

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 26 S., R. 2 W.

CHAINS

from which the remaining original 1883 McQuinn bearing trees

A burned fir snag, 54 ins. diam., bears S. 85* W.,
44 lks. dist., no marks visible. (record, 41 lks.)

A fir, 30 ins. diam., bears N. 55* W., 52 $\frac{1}{2}$ lks. dist.,
with portion of original bark scribes visible and
rescribed T26S R2W S12 CS BT on partially healed blaze
by the County Surveyor in 1945. (Record, 55 lks.)

and a bearing tree mkd. by the County Surveyor in 1945

A fir, 11 ins. diam., bears S. 47 $\frac{1}{4}$ * W., 21 lks. dist.,
mkd. with a healed blaze.

N. 1* 26' E., on the E. bdy. of sec. 12, marking and blazing
the true line.

Ascend 260 ft. over steep rocky S. slope, through heavy timber
and moderate undergrowth.

4.00 Top of rock bluff, edge bears E. and W.; asc. 200 ft. over S.
slope, changing to E. slope.

20.80 Creek, 3 lks. wide, course S. 40* E.; asc. 10 ft. over SW. slope.

22.75 Spring, drains S. 30* W., curving to S.; asc. 170 ft. over SW.
slope.

35.64 From this point, the $\frac{1}{4}$ sec. cor. of sec. 7 only, T. 26 S., R. 1
W., bears West 0.06 chs. dist., perpetuated and recorded by the
County Surveyor's Office in 1961 when the original weathered
corner stone, which is no longer in evidence, was existent,
monumented with an iron post, 1 in. diam., protruding 12 ins.
above the ground, firmly set in the original mound of stone,
2 ft. base, to top with brass cap marked.

COUNTY SURVEYORS OFFICE

T 26 S
 $\frac{1}{4}$ S 7
1961

from which the original 1910 Mensch bearing trees

A chinquapin, 20 ins. diam., bears N. 30* E.,
73 lks. dist., will illegible scribe marks
visible on partially opened blaze. (Record,
N. 28* E.)

A root crown, bears S. 68* E., 43 lks. dist.,
with a decayed madrone alongside, 7 ins. diam.,
no marks visible. (Record, S. 69* E.)

and a bearing tree mkd. by the County Surveyors Office in 1961

A cedar, 7 ins. diam., bears S. 86* E., 60 lks.
dist., with scribe marks $\frac{1}{2}$ S7 CS BT visible
on partially healed double blaze.

The corner falls at NW. cor. of timber, edges bear E. and S.

Ascend 13 ft. along W. slope, across logged area.

39.78 The $\frac{1}{4}$ sec. cor. of sec. 12 only, on the E. bdy. of the Tp.,
perpetuated and recorded by the County Surveyors Office in
1961 when the original weathered corner stone which is no longer
in evidence, was existent, monumented with an iron post, 1 in.
diam., protruding 12 ins. above the ground, firmly set, with brass
cap mkd.