

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T 26 S., R. 2 W

CHAINS

from which the original 1910 Mensch bearing trees

A root hole, bears S. 72* W., 44 lks. dist.,
with an uprooted fir alongside, 40 ins. diam.,
with a healed blaze.

A fir, 12 ins. diam., bears N. 33* W., 32 $\frac{1}{2}$ lks.
dist., with a healed blaze. (Record, 31 lks.)

and a bearing tree mkd. by the County Surveyors Office in 1961

A cedar, 12 ins. diam., bears S. 81 $\frac{1}{2}$ * W., 12 $\frac{1}{2}$ lks.
dist., with scribe marks T 26S R2W S12 CS BT
visible on partially healed double blaze.

The corner falls at NE. cor. of logged area, edges bear
S. and W.

Land, Mountainous

Soil, rocky clay.

Timber, fir, cedar, hemlock, alder, maple, madrone, yew, and
chinquapin; undergrowth, young timber, fern, salal, poison oak,
Oregon grape, rhododendron, manzanita, and mountain willow.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon

(Restoring the 1883 survey by John A. McQuinn)

From the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, perpetuated and
recorded by the County Surveyors Office in 1961, monumented
with an iron post, 1 in. diam., firmly set in a mound of stone,
3 ft. base, 2 ft. high, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 26 S R 2 W

 $\frac{1}{4}$ S 14 | S 13

1961

from which the original bearing trees

A fir snag, 21 ins. diam., bears N. 16* E.,
70 $\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S BT
visible on bark. (Record, N. 20* E., 69 lks.)

A fir, 43 ins. diam., bears N. 44 $\frac{1}{2}$ *W., 60 lks.
dist., rescribed $\frac{1}{4}$ S CS BT on partially healed
double blaze, no original scribe marks visible.
(Record, N. 40* W.)

and a bearing tree mkd. by the County Surveyors Office

A white oak, 6 ins. diam., bears N. 66* E.,
55 lks. dist., with scribe marks $\frac{1}{4}$ S13 CS BT
visible on partially healed double blaze.

The corner falls on top of large rock outcropping.

N. 2* 06' W., bet. secs. 13 and 14, marking and blazing
the true line.

Ascend 700 ft. over SE. slope and rock bluff, through medium
timber and moderate undergrowth, across partially logged area.