

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS

- 40.70 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 26 S R 2 W
 $\frac{1}{4}$
 S 11 | S 12
 1968
- from which
- A fir, 16 ins. diam., bears S. 64* E., 43 lks.
dist., mkd. $\frac{1}{4}$ S12 BT.
- A fir, 16 ins. diam., bears S. 64* W., 19 lks.
dist., mkd. $\frac{1}{4}$ S!! BT.
- Ascend 10 ft. along W. slope.
- 43.00 Spur, slopes W.; desc. 150 ft. over NW. slope.
- 52.00 Creek, 1 lks. wide, course S. 60* W.; asc. 185 ft. over S. slope.
- 60.00 Spur, slopes SW.; desc. 260 ft. over NW. slope.
- 71.80 Creek, 2 lks. wide, course W.; asc. 150 ft over S. slope, changing to SW. slope.
- 79.00 Spur, slopes W.; desc. 40 ft. over NW. slope.
- 81.40 The cor. of secs. 1, 2, 11, and 12, perpetuated and recorded by G. R. Lecklider, Registered Engineer No. 4079, in 1959, monumented with a fir post, 3 ins. diam., protruding 4 ft. above the ground, firmly set, from which the original bearing trees:
- A fir, 52 ins. diam., bears N. 58* E., 83 lks.
dist., with faint original bark scribing visible.
(Record, N. 50* E., 80 lks.)
- A fir snag, 48 ins. diam., bears S. $65\frac{1}{2}$ * E., 44 lks. dist., with faint original bark scribing visible and rescribed BT on bark blaze.
(Record, S. 60* E., 40 lks.)
- and bearing trees mkd. by Lecklider in 1959,
- A fir, 27 ins. diam., bears N. 47* E., $13\frac{1}{2}$ lks. dist., mkd. S1 R4079 on bark blaze and with healed blaze at base.
- A fir, 10 ins. diam., bears S. 18 $\frac{1}{2}$ * E., 9 lks. dist., with a pitched over double blaze.
- A fir, 10 ins. diam., bears S. 56 $\frac{1}{2}$ * W., $15\frac{1}{2}$ lks. dist., with scribe marks S11 R4079 BT visible on partially healed double blaze.
- A fir, 8 ins. diam., bears N. 30 $\frac{1}{2}$ * W., 25 lks. dist., with scribe marks S2 R4079 BT visible on partially healed double blaze.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.