

T. 21 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of a certain original corner point in T. 21 S., R. 7 W., Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, With New Accessories When Needed".

(Remonumentation of the Corner Established by William P. Wright in 1884)

The cor. of secs. 5, 6, 7, and 8, determined at record bearing and distance from the original bearing trees:

A hemlock, 28 ins. diam., bears N. 61° E. 35 lks. dist., with no marks visible on decayed blaze.

A decayed hemlock stump, 18 ins. diam., bears S. 12° W., 41 lks. dist., with no marks remaining.

A fir, 52 ins. diam., bears N. 13° W., 18 lks. dist., with fragmentary scribe marks visible on bark blaze. (Record, Hemlock)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S R 7 W
 S 6 S 5
 S 7 S 8
 1965

from which new bearing trees

A hemlock, 7 ins. diam., bears N. 31½° E., 69 lks. dist., marked T21S R7W S5 BT.

A hemlock, 10 ins. diam., bears S. 13° E., 25 lks. dist., marked T21S R7W S8 BT.

A hemlock, 12 ins. diam., bears S. 28° W., 34 lks. dist., marked T21S R7W S7 BT.

A hemlock, 25 ins. diam., bears N. 61° W., 64½ lks. dist., marked T21S R7W S6 BT.