

County Surveyor's Record, Douglas County, Oregon

T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of township 26 south, range 7 west, Willamette Meridian, Oregon, in the portion covered by this resurvey, is as follows:

A portion of the subdivisional lines was surveyed by Dennis Hathorn in 1855, as shown on the official plat of survey approved July 7, 1856. In 1881 Addison R. and Samuel C. Flint completed the survey of the subdivisional lines as shown on the official plat of survey approved January 14, 1882. In 1963 Donald R. Beck remonumented the corner of sections 9, 10, 15, and 16, and the $\frac{1}{2}$ section corner of sections 9 and 10, without survey.

Preliminary to the resurvey the lines of the original surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only lines bounding, or crossing, public lands were blazed. All lines not forming a closure were chained twice.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated September 24, 1957, under Group 357, Oregon.

The directions of lines were determined by the solar transit and solar compass methods.

The geographic position of the corner of sections 9, 10, 15, and 16, as scaled from the Tyee Quadrangle map, published by the United States Geological Survey in 1955, is as follows:

Latitude $43^{\circ} 19.0' N.$ Longitude $123^{\circ} 31.5' W.$

The mean magnetic declination is $19^{\circ} 15' E.$

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the 1855 survey by Dennis Hathorn,
the 1881 survey by Addison R. and Samuel C. Flint,
and the 1963 remonumentation by Donald R. Beck)

From the corner of secs. 9, 10, 15, and 16, monumented with and iron post, $2\frac{1}{2}$ ins. diam., protruding 4 ins. above the ground, firmly set, with brass cap marked and witnessed as described in the official record of the 1963 remonumentation.

N. $0^{\circ} 31' W.$, bet. secs. 9 and 10, marking and blazing the true line.

Ascend 1 ft. over nearly level ground, through heavy timber and dense undergrowth, along E. edge of logged area.

- | | |
|-------|---------------------------------------------------------------------------------------------|
| 0.75 | Rock outcropping, bears E. and W.; desc. 500 ft. over N. slope, changing to steep NE slope. |
| 12.55 | Wire fence, bears E. and W. |
| 13.00 | Dirt road, 15 lks. wide, bears E. and W. |