

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S., R. 7 W.

CHAINS

- 14.20 Wire fence, bears E. and W.
- 23.80 Bottom of descent, slopes NW.; asc. 100 ft. over SW. slope.
- 25.60 Rocky spur, slopes NW.; desc. 170 ft. over N.W. slope.
- 30.65 Dirt road, 20 lks. wide, bears N. 65° E. and S. 65° W.
- 35.00 Creek, 5 lks. wide, course N. from SW.; desc. 30 ft. over N. slope changing to W. slope, along creek.

40.32 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., protruding 8 ins. above the ground, firmly set, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 9 | \text{S } 10 \\ \text{T } 26 \text{ S } \text{ R } 7 \text{ W} \\ 1963 \end{array}$$

from which the remaining original bearing tree by Dennis Hathorn in 1855

A root hole, bears S. 67° W., 26 lks. dist., with a fallen cedar alongside, 24 ins. diam., with $\frac{1}{4}$ visible in negative on the overgrowth.

and bearing trees mkd. by Donal R. Beck in 1963

A root hole, bears S. 46 $\frac{1}{2}$ ° E., 26 lks. dist., with a fallen hemlock alongside, 13 ins. diam., with scribe marks $\frac{1}{4}$ S10 BT visible on open blaze.

A burned cedar stump, 18 ins. diam., bears N. 85 $\frac{1}{2}$ ° W., 34 lks. dist., no marks remaining.

and new bearing trees

A fir, 12 ins. diam., bears N. 88 $\frac{1}{2}$ ° E., 41 lks. dist., mkd. $\frac{1}{4}$ S10 BT.

A fir, 8 ins. diam., bears N. 11° W., 215 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 9 BT.

The corner falls on E. bank of creek, 5 lks. wide, course N. 5° E.

N. 0° 04' E., beginning new measurement.

Continue along creek.

- 2.20 Leave creek, course N. 30° W.; desc. 95 ft. over general N. slope.
- 9.00 Spring seepage, 2 lks. wide, course NW.; desc. 137 ft. along W. slope, changing to N. slope.
- 40.18 The cor. of secs. 3, 4, 9, and 10, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1959, monumented with an iron post, 1 in. diam., protruding 16 ins. above the ground, firmly set, with brass cap mkd:

$$\begin{array}{c} \text{COUNTY SURVEYORS OFFICE} \\ \text{T } 26 \text{ S } \text{ R } 7 \text{ W} \\ \text{S } 4 | \text{S } 3 \\ \text{S } 9 | \text{S } 10 \\ 1959 \end{array}$$