

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S., R. 7 W.

CHAINS

39.94

Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 7 W
 $\frac{1}{4}$
 S 8 | S 9
 1967

from which

A fir, 14 ins. diam., bears N. 46° E., $31\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S9 BT.

A fir, 23 ins. diam., bears S. 25° W., 32 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Descend 65 ft. along E. slope, changing to NE. slope.

55.00

Creek, 2 lks. wide, course E.; asc. 10 ft. over broken S.E. slope.

59.91

Point for the N $1/16$ sec. cor. of secs. 8 and 9.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

N $1/16$
 S 8 | S 9
 1967

from which

A fir, 12 ins. diam., bears S. 40° E., $76\frac{1}{2}$ lks. dist., mkd. N $1/16$ S9 BT.

A fir, 27 ins. diam., bears N. 22° W., $51\frac{1}{2}$ lks. dist., mkd. N $1/16$ S8 BT.

Ascend 60 ft. over SE. slope.

69.65

Spur, slopes E.; desc. 200 ft. over NE. slope.

79.88

The cor. of secs. 4, 5, 8, and 9, established by Flint in 1881, determined from the original bearing trees:

A fir, 22 ins. diam., bears N. $37\frac{3}{4}^\circ$ E., 48 lks. dist., with axe marks visible on opened blaze.
 (Record, N. 45° E., 59 lks.)

A decayed fir stump, 8 ins. diam., bears S. 5° E., 34 lks. dist., with old axe marks visible

A root hole, bears S. 80° W., 10 lks. dist., with a fallen fir alongside, 16 ins. diam., with opened and rotted blaze, no scribe marks visible.

A fir, 30 ins. diam., bears N. 20° W., 14 lks. dist., with scribe marks BT visible on partially opened blaze.

At the corner point