

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 29 S., R. 7 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
 S 21 | S 22
 S 28 | S 27
 1966

from which new bearing trees

A fir, 15 ins. diam., bears N. 80° E., 193 lks. dist., mkd. T29S R7W S22 BT.

A fir, 10 ins. diam., bears S. 69° W., 94 lks. dist., mkd. T29S R7W S28 BT.

A fir, 13 ins. diam., bears N. 18° W., 200 lks. dist., mkd. T29S R7W S21 BT.

N. 1° 02' W., bet. secs. 21 and 22, marking and blazing the true line.

Ascend 185 ft. over SW. slope, across logged area, through scattering timber and dense undergrowth.

8.00 Spur, slopes S. 55° E.; asc. 5 ft. along E. slope.

19.91 Point for the S 1/16 sec. cor. of secs. 21 and 22.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
 S 21 | S 22
 1966

from which

A fir, 13 ins. diam., bears S. 37½° E., 60 lks. dist., mkd. S 1/16 S22 BT.

A fir, 13 ins. diam., bears N. 73½° W., 59 lks. dist., mkd. S 1/16 S21 BT.

Ascend 35 ft. along an E. slope.

28.90 Ravine, drains S. 25° E.; asc. 245 ft. over S. slope, changing to SW. slope.

38.00 Leave logged area; enter timber, edge bears generally E. and W.

39.82 Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
 ¼
 S 21 | S 22
 1966

*FD. B.C. 2 BTs
 10/84 H. J. JOHNSON
 M 97-54*

from which

A fir, 23 ins. diam., bears N. 89° E., 15½ lks. dist., mkd. ¼ S22 BT.