

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T.29 S., R. 7 W.

CHAINS

19.42

Point for the E 1/16 sec. cor. of secs. 21 and 28.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$E \frac{1}{16} \begin{array}{l} S 21 \\ S 28 \end{array}$$
 1966

from which

A pine, 21 ins. diam., bears N. 71½° W., 48 lks. dist., mkd. E 1/16 S21 BT.

A pine, 16 ins. diam., bears S. 51° W., 31 lks. dist., mkd. E 1/16 S28 BT.

Descend 275 ft. over W. slope, changing to NW. slope.

38.84

The ¼ sec. cor. of secs. 21 and 28, determined at record bearing and distance from the original bearing trees:

An oak root crown, size indeterminate, bears N. 72° W., 94 lks. dist., no marks remaining.

A down oak, 14 ins. diam., bears S. 64° E. 62 lks. dist., with scribe marks ¼ S BT visible in negative on rotted overgrowth.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$T 29 S R 7 W$$

$$\frac{1}{4} \begin{array}{l} S 21 \\ S 28 \end{array}$$
 1966

 FO. OK 3/92  
 L. HERZSTEIN  
 M 11A-65

from which new bearing trees

A white fir, 21 ins. diam., bears N. 58° E., 86 lks. dist., mkd. ¼ S21 BT.

A fir, 8 ins. diam., bears S. 60° E., 43 lks. dist., mkd. ¼ S28 BT.

N. 89° 02' W., beginning new measurement.

Descend 185 ft. over NW. slope.

11.15

Ravine, drains S. 50° W.; desc. 100 ft. over W. slope.

29.68

Barbed wire fence, bears N. and S., leave logged area; enter cultivated field, edge bears N. and S.

36.80

Leave cultivated field; enter logged area, edge bears N. and S.

37.78

Barbed wire fence, bears N. and S.

39.72

The cor. of secs. 20, 21, 28 and 29, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1954, monumented with an iron pipe, 1 in. diam., firmly set, extending 4 ins. above the ground, with brass cap mkd.