

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 29 S., R. 7 W.

## CHAINS

- 57.165 Point for the W 1/16 sec. cor. of secs. 16 and 21.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- W 1/16  $\frac{S\ 16}{S\ 21}$   
1966
- from which
- A fir, 14 ins. diam., bears N. 53½° W., 30 lks. dist., mkd. W 1/16 S16 BT.
- A fir, 18 ins. diam., bears S. 41½° E., 29 lks. dist., mkd. W 1/16 S21 BT.
- Descend 50 ft. over W. slope.
- 64.35 Olalla Creek, 30 lks. wide, course N. 65° W/; asc. 195 ft. over general E. slope.
- 67.25 Bridge over Olalla Creek, on county road, paved surface, 30 lks. wide, bears N. and S.
- 76.22 The cor. of secs. 16, 17, 20 and 21.
- Land, mountainous.  
Soil, rocky clay loam.  
Timber, fir, cedar, pine, oak, maple, madrone, alder and chinquapin; undergrowth, vine maple, hazel, poison oak, ocean spray, fern Oregon grape, huckleberry, and blackberry.
- Subdivision of Section 21, T. 29 S., R. 7 W.,  
Willamette Meridian, Oregon
- From the ¼ sec. cor. of secs. 21 and 28.
- N. 0° 31' W., on the N. and S. center line of sec. 21.
- Descend 20 ft. over N. slope, across logged area, through scattering timber and dense undergrowth.
- 1.40 Ravine, drains N. 70° W.; asc. 15 ft. over SW. slope.
- 3.50 Top of ascent, slopes W.; desc. 15 ft. over NW. slope.
- 5.40 Ravine, drains SW.; asc. 60 ft. over SW. slope.
- 11.25 Dirt road, 10 lks. wide, bears N. 80° E. and S. 80° W.
- 12.80 Top of ascent, slopes W.; desc. 45 ft. over NW. slope.
- 16.10 Ravine, drains W.; asc. 45 ft. over SW. slope.
- 19.94 Point for the center S 1/16 sec. cor. of sec. 21.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- S 1/16  $\frac{C}{S\ 21}$   
1966