

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 21, T. 29 S., R. 7 W.

CHAINS

from which

A madrone, 11 ins. diam., bears S. 66° E., 84 lks. dist., mkd. CS 1/16 S21 BT.

A fir, 8 ins. diam., bears N. 23° W., 23 lks. dist., mkd. CS 1/16 S21 BT.

Ascend 60 ft. over SW. slope.

26.00 The SW. cor. of old growth timber, edges bear generally N. and E.; thence along the E. edge of logged area.

27.50 Spur, slopes W.; desc. 140 ft. over NW. slope.

33.20 Ravine, drains S. 70° W.; asc. 130 ft. over S. slope; also the NE. cor. of logged area, edges bear generally S. and W.; thence through heavy timber and dense undergrowth.

35.40 Top of rock bluff, 50 ft. high, bears E. and W.; asc. 90 ft. over SW. slope.

39.88 Point for the center $\frac{1}{4}$ sec. cor. of sec. 21, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C $\frac{1}{4}$ S21
1966

from which

A fir, 24 ins. diam., bears S. 85° E., 27 lks. dist., mkd. C $\frac{1}{4}$ S21 BT.

A madrone, 16 ins. diam., bears N. 50° W., 80 lks. dist., mkd. C $\frac{1}{4}$ S21 BT.

Ascend 15 ft. over SW. slope.

42.50 Spur, slopes W.; desc. 355 ft. over NW. slope.

54.25 Creek, 1 lk. wide, course S. 80° W.; asc. 120 ft. over S. slope.

59.79 Point for the center N 1/16 sec. cor. of sec. 21.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16 $\begin{matrix} C \\ | \\ S \\ | \\ C \end{matrix}$ 21
1966

from which

A fir, 7 ins. diam., bears N. 83° E. 27 lks. dist., mkd. CN 1/16 S21 BT.

A fir, 20 ins. diam., bears N. 25° W., $12\frac{1}{2}$ lks. dist., mkd. CN 1/16 S21 BT.

Ascend 460 ft. over S. slope.