

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 23 S., R. 1 W.

CHAINS

A hemlock, 44 ins. diam., bears S. 38° W., 33 lks. dist., with scribe marks 2 B visible on partially healed blaze. (Record, and dist. to face, 30 lks.)

A white fir, 38 ins. diam., bears N. 68° W., 36 lks. dist. with scribe marks S30 T23 R2 BT visible on open blaze. (Record, and dist. to face, 33 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 23 S
R 2 W R 1 W
S 36 S 31
S 1 S 6
T 24 S
1964

from which

A white fir, 17 ins. diam., bears N. 33½° E., 46 lks. dist., mkd. T23S RW S31 BT.

N. 1° 34' W., bet. secs. 31 and 36, on the W. bdy of the Tp., marking and blazing the true line.

Descend 106 ft. over steep NE. slope, through heavy timber and light undergrowth.

- 3.29 Spring seepage, 1 lk. wide, course N. 75° E.; desc. 122 ft. over NE. slope.
- 8.22 Creek, 1 lk. wide, course N. 60° E.; asc. 93 ft. over SE. slope.
- 15.22 Spur, slopes N. 60° E.; desc. 712 ft. over NE. slope.
- 24.10 Top of rock bluff, 50 ft. high, edge bears NW. and SE.
- 35.97 From this point, a corner established by John A McQuinn, in 1883, bears East, 0.418 chs. dist., determined from the original bearing trees:
- A cedar, 34 ins. diam., bears East, 61 lks. dist., with healed blaze. (Record, and dist. to face, 58 lks.)
- A fir snag, 28 ins. diam., bears S. 87° W., 25 lks. dist., with scribe marks ½ S visible on bark blaze. (Record, and dist. to face, 23 lks.)
- This corner was superseded by Chandler's survey.
- 36.75 Creek, 5 lks. wide, course N. 40° E.; asc. 67 ft. over SE. slope.
- 39.55 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S
R 2 W R 1 W
S 36 S 31
1964

from which