

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 23 S., R. 1 W.

CHAINS

Dependent Resurvey of a Portion of the North Boundary, T. 23 S., R. 1 W., Willamette Meridian, Odegon

(Restoring the 1891 survey by William M. Bushey and the 1960 resurvey by Harold D. Corbin)

From the cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 2½ ins. diam., firmly set, 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 S R 1 W
 S 35 | S 36
 S 2 | S 1
 T 23 S
 1960

from which the remains of the original bearing trees

A fir, 27 ins. diam., bears N. 31° E., 33 lks. dist., with healed blaze. (Record, N. 35° E., 35 lks.)

A fir, 47 ins. diam., bears S. 57½° E., 69 lks. dist. with partially healed blaze, no marks visible. (Record, S. 60° E., 71 lks.)

A sawed fir stump, 28 ins. diam., bears S. 77½° W., 36 lks. dist., no marks visible. (Record, S. 74½° W., 33 lks.)

A fir, 26 ins. diam., bears N. 74° W., 34 lks. dist. with healed blaze. (Record, N. 74½° W., 31 lks.)

and a tree by Corbin

A fir snag, 12 ins. diam., bears S. 61 ¾° W., 47 lks. dist., with scribe marks T23S RLW S2 BT. visible on partially healed blaze. (Record, S. 60° E.)

and a ^{new} bearing tree

A fir, 16 ins. diam., bears S. 13° W., 111 lks. dist. mkd. T23S RLW S2 BT.

S 89° 21' W., bet. secs. 2 and 35, marking and blazing the true line.

Descend 385 ft. over SW. slope, through scattering timber and dense undergrowth.

25.10 Sharps Creek, 40 lks. wide, course NW.; asc. 350 ft. over general E. slope.

26.50 Sharps Creek Road, 25 lks. wide, bears NW. and SE.

38.80 Dirt road, 25 lks. wide, bears NW. and SE., curving to NE.

39.19 The ¼ sec. cor. of secs. 2 and 35, monumented with an iron post, 2½ ins. diam, firmly set, protruding 6 ins. above ground, with brass cap marked and witnessed as described in the record of the 1960 dependent resurvey.