

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Partion of N. Bdy., T. 23 S., R. 1 W.

CHAINS

S. 89° 42' W., bet. secs. 5 and 32.

Ascend 10 ft. over E. slope, across logged area, through scattering timber and light undergrowth.

2.30 Ridge, divides Sharps Creek and Mosby Creek drainages, bears N. 10° W. and S. 5° E.; desc. 340 ft. over SW. slope.

3.75 Gravelled road, 30 lks. wide, bears N. 60° W. and S. 60° E.

10.15 Leave logged area, enter heavy timber and moderate undergrowth edge bears N. and S.

20.35 Top of rock bluff, 210 ft. high, bears N. 60° W. and S. 60° E.; desc. 255 ft. over bluff and W. slope.

25.20 Creek, 4 lks. wide, course N. 20° W.; asc. 35 ft. over NE. slope.

29.75 ^opur, slopes N. 20° W.; desc. 160 ft. over NW. slope.

39.52 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 S R 1 W
 $\frac{1}{4}$ S 32
 $\frac{1}{4}$ S 5
 T 23 S
 1966

from which

A cedar, 10 ins. diam., bears N. 68° E., 35 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A fir, 38 ins. diam., bears S. 32 $\frac{1}{2}$ ° W., 71 lks. dist. mkd. $\frac{1}{4}$ S5 BT.

Descend 445 ft. over NW. slope.

59.28 Point for the W. 1/16 sec. cor. of secs. 5 and 32.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 32
 W 1/16 $\frac{S}{5}$
 1966

from which

A cedar, 32 ins. diam., bears N. 57 $\frac{1}{4}$ ° W., 56 $\frac{1}{2}$ lks. dist. mkd. W1/16 S32 BT.

A cedar, 24 ins. diam., bears S. 63 $\frac{1}{4}$ ° W., 33 lks. dist. mkd. W1/16 S5 BT.

Descend 190 ft. over NW. slope.