

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS

T 23 S R 1 W
 S 3 | S 2
 S 10 | S 11
 1964

from which

- A fir, 25 ins. diam., bears N. $16\frac{1}{4}^{\circ}$ E., 75 lks. dist.,
 mkd. T23S R1W S2 BT.
- A fir, 7 ins. diam., bears S. $71\frac{3}{4}^{\circ}$ E., $31\frac{1}{2}$ lks. dist.,
 mkd. T23S R1W S11 BT.
- A fir, 8 ins. diam., bears S. $2\frac{1}{4}^{\circ}$ W., $46\frac{1}{2}$ lks. dist.,
 mkd. T23S R1W S10 BT.
- A cedar, 33 ins. diam., bears N. 67° W., 82 lks. dist.,
 mkd. T23S R1W S3 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, alder, maple, cascara, yew,
 madrone, chinquapin, pine, and oak; undergrowth, vine maple,
 hazel, rhododendron, arrowwood, huckleberry, salal, Oregon grape,
 wild rose, blackberry, poison oak, sword fern and bracken.

From the cor. of secs. 1, 2, 11, and 12.

S. $89^{\circ} 12'$ W., bet. secs. 2 and 11.Descend 75 ft. over NW. slope, through heavy timber and
dense undergrowth.

- 1.40 Creek, 2 lks. wide, course N. 10° W.; asc. 105 ft. over NE.
slope.
- 3.90 Spur, slopes NW.; desc. 260 ft. over NW. slope, changing to
N. slope.
- 15.55 Walker Creek, 10 lks. wide, course N. 40° E.; asc. 20 ft. over
SE. slope.
- 18.85 Creek, 2 lks. wide, course S. 60° E.; asc. 405 ft. over SE.
slope.
- 32.05 Spur, slopes E.; asc. 65 ft. along back of spur,
- 36.15 Leave back of spur, slopes E.; asc. 60 ft. over NE. slope.
- 39.09 The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, monumented with a monel
pipe, $\frac{5}{8}$ in. diam., firmly set, protruding 10 ins. above ground,
from which the original bearing trees:
- A fir 72 ins. diam., bears N. 70° W., 13 lks. dist.
with scribe mark I visible on bark blaze. This tree has
been remarked $\frac{1}{4}$ S on bark blaze.
- A hemlock, 25 ins. diam., bears S. 50° E., 24 lks. dist.,
with scribe mark T visible on bark blaze. This tree
has been remarked $\frac{1}{4}$ S on bark blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the
ground, with brass cap mkd.