

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S. R. 1 W.

CHAINS

T 23 S R 1 W

S 2
S 11

1964

Reset monel pipe alongside iron post.

S. 88° 22' W., beginning new measurement.

Ascend 60 ft. over NE. slope.

3.70 Spur, slopes S. 60° E.; desc. 130 ft. over SW. slope.

6.95 Ravine, drains S. 10° W.; asc. 65 ft. over SE. slope.

10.10 Spur, slopes S. 10° W.; desc. 95 ft. over SW. slope.

13.80 Ravine, drains S.; asc. 35 ft. over SE. slope.

14.75 Spur, slopes S.; desc. 100 ft. over SW. slope.

20.50 Creek, 2 lks wide, course S. 60° E.; asc. 290 ft. over NE. slope.

26.90 Spur, slopes S. 50° E.; asc. 430 ft. over SE. slope.

39.97 The cor. of secs. 2, 3, 10, and 11.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder maple, yew, cascara, chinquapin, madrone, dogwood, pine, and oak; undergrowth, vine maple, hazel, arrowwood, rhododendron, huckleberry, blackberry, wild rose, salal, Oregon grape, poison oak, sword fern and bracken.

N. 2° 08' W., bet. secs. 2 and 3.

Ascend 85 ft. over SE. slope, through heavy timber and moderate undergrowth.

7.70 Head of ravine, drains E.; asc. 75 ft. over SE. slope.

11.95 Spur, slopes E.; desc. 45 ft. over NE. slope.

14.10 Head of ravine, drains S. 80° E.; asc. 20 ft. over SE. slope.

15.35 Spur, slopes S. 80° E.; desc. 55 ft. over NE. slope.

18.10 Ravine, drains S. 50° E.; asc. 75 ft. over SE. slope.

20.09 Point for the S 1/16 sec. cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 3/16 S 2
1964

from which

A fir, 7 ins. diam., bears N. 89½° E., 30½ lks. dist., mkd. S1/16 S2 BT.