

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS

- 22.85 Bottom of same bluff, bears NE. and SW.; desc. 175 ft. over NW. slope.
- 27.00 Head of ravine, drains N.; asc. 90 ft. over NE. slope.
- 31.60 Spur, slopes N.; desc. 640 ft. over NW. slope.
- 40.30 Point for the  $\frac{1}{4}$  sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.
- No permanent monument established.
- 49.50 Walker Creek, 10 lks. wide, in bed 45 lks. wide, course N.; asc. 945 ft. over general E. slope.
- 71.90 Spur, slopes N.  $50^{\circ}$  E.; desc. 25 ft. over NW. slope.
- 80.60 Point for the cor. of secs. 9, 10, 15, and 16, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long.  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

|              |
|--------------|
| T 23 S R 1 W |
| S 9   S 10   |
| S 16   S 15  |
| 1966         |

from which

- A hemlock, 22 ins. diam., bears N.  $49\frac{1}{4}^{\circ}$  E., 36 lks. dist., mkd. T23S R1W S10 BT.
- A hemlock, 14 ins. diam., bears S.  $9\frac{1}{4}^{\circ}$  E., 62 lks. dist. mkd. T23S R1W S15 BT.
- A hemlock, 10 ins. diam., bears S.  $14\frac{3}{4}^{\circ}$  W.,  $41\frac{1}{2}$  lks. dist., mkd. T23S R1W S16 BT
- A fir, 42 ins. diam., bears N.  $14\frac{1}{2}^{\circ}$  W.,  $24\frac{1}{2}$  lks. dist., mkd. T23S R1W S9 BT.

From this point the cor. of secs. 15, 16, 21, and 22, bears S.  $2^{\circ} 56' W.$ , 80.45 chs. dist., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.

|              |
|--------------|
| T 23 S R 1 W |
| S 16   S 15  |
| S 21   S 22  |
| 1960         |

from which the remains of the original bearing trees

- A fir snag, 33 ins. diam., bears N.  $52^{\circ}$  E., 46 lks. dist., with illegible scribe marks visible on bark blaze.
- A hemlock, 15 ins. diam., bears S.  $28\frac{1}{2}^{\circ}$  E., 42 lks. dist. with illegible scribe marks visible on partially opened blaze.
- A root hole bears S.  $57\frac{1}{2}^{\circ}$  W., 29 lks. dist., with a down hemlock alongside, 13 ins. diam., with scribe marks 3 21 visible on partially opened blaze.