

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS

39.94

The  $\frac{1}{4}$  sec. cor. of secs. 8 and 9, reestablished at proportionate distance be Georgia-Pacific Corporation, monumented with an iron pipe, 1 in. diam., firmly set, protruding 5 ins. above ground, from which:

A fir, 44 ins. diam., bears S. 72° E., 11 $\frac{1}{2}$  lks. dist., with scribe marks  $\frac{1}{4}$  S9 CS BT visible on open blaze.

A sawed fir stump, 44 ins. diam., bears S. 25° W., 19 $\frac{1}{2}$  lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 18 ins. in the ground, and in a mound of stone, 2 $\frac{1}{2}$  ft. base, to top, with brass cap mkd.

T 23 S R 1 W  
 $\frac{1}{4}$   
 S 8 | S 9  
 1966

from which a new bearing tree

A fir, 12 ins. diam., bears N. 38° W., 70 lks. dist., mkd.  $\frac{1}{4}$  S8 BT.

Reset the iron pipe alongside the iron post.

N. 2° 34' W., beginning new measurement.

Ascend 5 ft. over SW. slope.

5.50 Spur, slopes W.; desc. 290 ft. over NW. slope.

22.50 Creek, 2 lks. wide, course W.; asc. 60 ft. over SW. slope.

31.75 Creek, 4 lks. wide, course S. 25° W.; asc 170 ft. over SE. slope.

39.99 The cor. of secs. 4, 5, 8, and 9, reestablished at proportionate postion and recorded by Ralph L. Follett, Registered Engineer, in 1957, monumented with an iron pipe, 2 $\frac{1}{2}$  ins. diam., firmly set protruding 14 ins. above ground, from which:

A root hole bears N. 83 $\frac{1}{4}$ ° E., 39 $\frac{1}{2}$  lks. dist., with a down yew alongside, 24 ins. diam., with scribe marks T23S RLW. S4 CS BT visible on open blaze.

A root hole bears S. 30° E., 45 lks. dist., with a down yew alongside, 20 ins. diam., with scribe marks T23S RLW S9 CS BT visible on open blaze.

A yew, 21 ins. diam., bears S. 89 $\frac{1}{4}$ ° W., 69 lks. dist., with scribe marks T23S RLW S8 Cs BT. visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.

T 23 S R 1 W  
 $\frac{1}{4}$   
 S 5 | S 4  
 S 8 | S 9  
 1966

from which new bearing trees