

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S. R. 1W.

CHAINS

S. 89° 19' W., bet. secs. 6 and 7.

Ascend 25 ft. over SE. slope, through heavy timber and moderate undergrowth.

2.20 Spur, slopes S. 10° W.; desc. 150 ft. over broken SW. slope.

7.60 Head of ravine, drains S. 10° W.; asc. 75 ft. over SE. slope.

17.35 Head of ravine, drains S.; asc. 290 ft. over SE. slope.

26.70 Spur ridge, dividing Shea Creek and Norwegian Creek drainages, bears N. 60° E. and S. 60° W.; desc. 355 ft. over NW slope.

39.625 The 1/4 sec. cor. of secs. 6 and 7, reestablished and recorded by Georgia-Pacific Corporation in 1961, monumented with an iron pipe, 1 1/2 ins. diam, firmly set, protruding 10 ins. above ground, from which:

A cedar, 34 ins. diam., bears N. 87° W., 62 1/2 lks. dist., with scribe marks CS BT visible on open blaze.

A cedar, 12 ins. diam., bears S. 4° E., 19 lks. dist., with scribe marks CS BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 1 W

1/4 S 6
S 7

1966

Reset the iron pipe alongside the iron post.

S. 89° 29' W., beginning new measurement.

Descend 120 ft. over NW. slope.

1.10 Head of ravine, drains N. 40° W.; asc. 90 ft. over NE. slope.

8.40 Spur, slopes N. 20° W.; desc. 115 ft. over NW. slope.

11.80 Head of ravine, drains N. 30° W.; asc. 30 ft. over NE. slope.

13.90 Spur, slopes N. 30° W.; desc. 65 ft. over NW. slope.

18.80 Spur, slopes N. 30° W.; desc. 150 ft. over NW. slope.

25.90 Ravine, drains N. 40° W.; asc. 40 ft. over NE. slope.

26.30 Top of ascent, slopes N.; desc. 80 ft. over NW. slope.

32.40 Ravine, drains N. 30° W.; desc. 60 ft. over NW. slope.

39.40 Ravine, drains N.; asc. 5 ft. over NE. slope.

39.625 Point for the 80 1/16 sec. cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/16 S 6
S 7 80
1966

from which