

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 1 W.

CHAINS

From the cor. of secs. 5, 6, 7, and 8.

N. 0° 40' E., bet. secs. 5 and 6.

Ascend 340 ft. over general S. slope, through heavy timber and moderate undergrowth.

10.50 Spur ridge, dividing Shea Creek and Norwegian Creek drainages, bears N. 75° E. and S. 75° W.; desc. 550 ft. over NW. slope.

26.80 Ravine, drains N. 20° W.; desc. 160 ft. over NW. slope.

32.25 Norwegian Creek, 4 lks. wide, course N. 75° W.; asc. 235 ft. over SW. slope.

38.64 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, reestablished locally and monumented with an iron pipe, 2 ins. diam., firmly set, protruding 26 ins. above ground, from which:

A fir, 26 ins. diam., bears N. 62 $\frac{1}{2}$ ° E., 60 $\frac{1}{2}$ lks. dist., with scribe marks CS BT visible on open blaze.

A fir, 18 ins. diam., bears N. 79° W., 48 lks. dist., with scribe marks CS BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 $\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T 23 S R 1 W
 $\frac{1}{4}$
 S 6 | S 5
 1966

Reset the iron pipe alogside the iron post.

N. 0° 19' E., beginning new measurement.

Ascend 460 ft. over SW. slope.

16.00 Spur ridge dividing Norwegian Creek and Dahl Creek drainages, bears E. and W.; desc. 120 ft. over NW. slope.

19.435 Point for the N 1/16 sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 $\frac{1}{4}$ ins. in the ground, with brass cap mkd.

N 1/16
 S 6 | S 5
 1966

from which

A fir, 22 ins. diam., bears N. 11 $\frac{1}{2}$ ° E., 11 $\frac{1}{2}$ lks. dist., mkd. N1/16 S5 BT.

A fir, 20 ins. diam., bears N. 50° W., 18 $\frac{1}{2}$ lks. dist., mkd. N1/16 S6 BT.

Descend 115 ft. over NW. slope.