

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 27 S., R. 9 W., W. M. (continued)

CHAINS

N. 89° 40' E. on a random line bet. secs. 24 and 25.

40.00 Set Temp 1/4 Sec. Cor.

80.39 Intersect E. Bdy of the Tp. 135 lks. S. of cor. to Secs. 19, 24, 25 and 30, which is a post, 12 ins. above ground, firmly set and mkd: T.27S. S 19 on N. E.,; R.8W. S.30 on S. E.; R.9W. S.25 on S. W. and S.24 on N.W. faces with 2 notches on S. and 4 notches on N. edges, from which:

A Fir, 24" diam bears N.28°E. 16 lks. dist. mkd:
T.27S. R.8 W. S.19 B. T.A Fir, 24 " diam bears S.8 1/2° E. 56 lks. dist. mkd:
T.27S. R.8W. S.30 B. T.A Fir, 36" diam. bears S.33°W. 36 lks. dist. mkd:
T.27S. R.9W. S25 B.T.A Fir, 50" diam. bears N.14°W. 30 lks. dist. mkd:
T.27S. R.9W. S24 B.T.

This correction placing one out of limits of allowable error, to ascertain cause, I carefully-remeasure the line between Sections 25 and 26 , and finding it practically correct, rechain the East Boundary of Section 25 and find its length to be 81.26 chains. The result showing the correctness of my position. I efface the markings on the established corner referring to sections in R.9 W. and at point of intersection:

St a sandstone 18 x 10 x 4 ins., 12 ins. in the ground for closing corner of Secs. 24 and 25, marked C.C. on W. face, with 2 grooves on S. & 4 grooves on N. face, from which:

A Fir, 30 ins. diam. bears S. 51° W. 27 lks. dist.
marked T.27S. R.9W. S25 B.T.A fir, 36 ins. diam. bears N. 85° W. 93 lks. dist.
marked T. 27 S. R.9W. S.24 B.T.

June 24, 1897

June 26 at 8 H. 00M a.m. l.m.t., I set off 43°13' N. on the lat. arc. 23° 22' N. on the decl. arc. and determine a true meridian with the solar at the cor. of Secs. 13, 14, 23 and 24.

N. 89° 40" E. on a random line bet. Secs. 13 and 24.

40.00 Set Temp 1/4 Sec. Corner.

79.94 Intersect E. bdy. of Tp. 3.01 chains S. of the Cor. of Secs. 13, 18, 19 and 24, which is a post, 12 in. above ground, firmly set marked T.27 S. S18 on N.E., R.8W. S.19 on S.E., R.9W. S.24 on S.W. and S.13 on N.W. faces with 3 notches on N. and S. edges , from which:

A Hemlock, 12" diam bears N.57 1/2° E. 40 lks. dist. mkd.
T.27S. R.8W. S18 B.T.A Hemlock, 24" diam. bears S. 22° E. 49 lks. dist. mkd.
T.27S. R.8W. S19 B.T.A Hemlock, 20" diam. bears S. 60° W. 27 lks. dist. mkd:
T.27S. R.9W. S.24 B.T.A Fir, 40" diam. bears N.18 1/4° W. 90 lks. dist. mkd:
T.27S. R.9W. S13 B.T.

This falling apparently places me out the limit of allowable error, but in view of the result of my remeasurement of the East boundary of Secs. 25 and 36, which shows irregular but long chaining along the E. boundary of this Tp., I deem any further remeasurements unnecessary. Therefore, I destroy the markings on this corner referring to Secs. in R. 9 W., and a point of intersection, I set a Sandstone 16 x 14 x 4 ins., 11 ins. in the ground for closing corner of Sec. 13 and 24, mark C.C. on W. with 3 grooves on N. and S. faces from which: