

County Surveyor's Record, Douglas County, Oregon

-Subdivision of T. 27 S., R. 9 W., W. M. (continued)

CHAINS

A Yew, 7 ins. diam. bears N. 36° W. 30 lks. dist. marked:
T.27S. R.9W. S. 13 B. T.
A Hemlock, 40 ins. diam. bears S. 64° W. 11 chains dist. marked:
T.27S. R.9W. S.24 B.T.

June 27 at 7 hs. am. l.m.t., I set off 43° 14' N. on the Lat. arc 23° 20' on the decl arc and determine a true meridian with solar at corner of Secs. 11, 12, 13 & 14.

N. 89° 40' E. on a random line bet. Secs. 12 and 13.

40.00 Set Temporary 1/4 Sec. Cor.

79.81 Intersect East boundary of the Tp. 3.15 chains S. of corner to Sections 7, 12, 13 and 18 which is a post, 12 ins. above ground, firmly set, marked: T.27S. S.7 on N.E.: R.8W. S.18 on S. E.; R.9W. S.13 on S.W. and Sec. 12 on N.W. faces with 4 notches on S. and 2 notches N. edges, from which:

A Fir, 36" diam. bears N.35 3/4° E. 16 lks. dist. mkd:
T.27S. R.8W. S. 7

A Fir, 30" diam. bears S. 20° E. 45 lks. dist. mkd:
T.27S. R.8W. S. 18

A Hemlock, 5" diam. bears S. 64° W. 40 lsk. dist. mkd:
T.27 S. R.9W. S. 13.

A Hemlock, 8" diam. bears N. 31° W. 36 lks. dist. mkd:
T.27S. R.9W. S. 12.

I efface the marking thereon referring to the Sections in R.9W., and at point of intersection, set a Sandstone, 18x12x7 ins., 12 ins. in the ground, for closing corner of Secs. 12 and 13, marked C.C. on W. with 4 grooves on S. and 2 grooves on N. face, from which:

A Yew, 12 ins. diam. bears N. 5° W. 10 lks. dist. mkd:
T. 27 S. R. 9 W. S. 12 B. T.

A Hemlock, 28 ins. diam. bears S. 20° W. 33 lks. dist. mkd:
T. 27 S. R. 9 W. S. 13 B. T.

June 28, at 7 hs. 00 m a.m. l.m.t., I set off 43° 15' N. on the lat. arc. 23° 17' N. on the decl arc and determine a true mendian with the solar at the corner of secs. 1, 2, 11 and 12.

N. 89° 40" E. on a random line bet. sections 1 and 12.

40.00 Set Temp. 1/4 Section Corner.

79.87 Intersect E. boundary of Tp. 5.90 chains S. of corner to Sections 1, 6, 7 and 12, which is a myrtle post, 12 ins. above ground, firmly set, marked: T.27S. S. 6 on N. E.: R. 8 W. S. 7 on S. E. R. 9W. S.12 on S.W. and S. 1 on N.W. faces with 5 notches on S. and 1 notch on W. edges, from which:

A Madrona, 16 ins. diam. bears N. 83° E. 110 lks. dist. mkd:
T.27S. R.8 W. S. 6 B. T.

A Fir, 40" diam. bears S. 5 1/2° E. 20 lks.dist. mkd:
T.27S. R.9W. S. 7 B.T.

A fir, 7: diam. bears S. 15 1/4° W. 45 lks. dist. mkd:
T.27S. R.9W. S.12 B.T.

A Fir, 18" diam. bears N.70° W. 50 lks. dist. mkd:
T.27S. R.9W. S. 1 B. T.