

## County Surveyor's Record, Douglas County, Oregon

T. 30 S., R. 6 W., Willamette Meridian, Oregon

## CHAINS

The history of surveys of township 30 south, range 6 west, Willamette Meridian, Oregon, in the portion covered by this resurvey, is as follows:

The north boundary was surveyed by Nathaniel Ford in 1854 as shown on the official plat of survey approved March 9, 1855. Addison R. Flint surveyed the subdivisional lines in 1855 as shown on the official plat of survey approved December 10, 1855. Hans W. Thielsen and C. Albert White dependently resurveyed the north boundary of sections 4 and 5 in 1958-59 as shown on the official plat of survey accepted March 1, 1961.

Preliminary to the resurvey the lines of the original surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only the lines bounding, or crossing, public lands were blazed. All lines were measured twice.

The directions of lines were determined by the solar transit method.

The geographic position of the  $\frac{1}{4}$  section corner of sections 15 and 16, as scaled from the Canyonville Quadrangle map, published by the United States Geological Survey in 1954, is as follows:

Latitude  $42^{\circ} 57.8' N.$  Longitude  $123^{\circ} 24.4' W.$

The mean magnetic declination is  $19^{\circ} 00' East.$

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the 1855 survey by Addison R. Flint)

From the  $\frac{1}{4}$  sec. cor. of secs. 15 and 16, perpetuated and recorded by R. M. Thompson, Registered Engineer No. 3683, in 1958, again perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 in. diam., protruding 18 ins. above ground, firmly set in a mound of stone, 3 ft. base, to top, with brass cap mkd.

## COUNTY SURVEYORS OFFICE

T 30 S  
 $\frac{1}{4}$   
 S 16 | S 15  
 R 6 W  
 1963

from which the original bearing trees

A stump hole, bears S.  $80^{\circ} E.$ , 188 lks. dist., with fallen and rotted pine alongside, 40 ins. diam., with scribe marks BT visible on opened blaze.

A stump hole, bears N.  $85^{\circ} W.$ , 300 lks. dist., with fallen and rotted black oak alongside, 24 ins. diam., with no marks visible.

and a bearing tree mkd. by Thompson in 1958