

Dependent Resurvey, Portion Subdivisional lines, T. 30 S., R. 6 W.

CHAINS

A cedar, 21 ins. diam., bears N. 42° E., $95\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S15 BT 3683 visible on open double blaze.

and a bearing tree mkd. by Byron in 1963

A cedar, 12 ins. diam., bears N. $89\frac{1}{4}^{\circ}$ W., $151\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S16 CS BT visible on open blaze.

N. $1^{\circ} 50'$ E., bet. secs. 15 and 16, marking and blazing the true line.

Ascend 40 ft. over S. slope, across partially logged area, through scattering timber and moderate undergrowth.

5.00 Top of ascent, slopes E.; desc. 10 ft. over NE. slope.

7.80 Jerry Creek, 6 lks. wide, course S. 60° E. from NW.; asc. 290 ft. over S. slope changing to SE. slope.

19.89 Point for the N $1/16$ sec. cor. of secs. 15 and 16.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

N $1/16$
S 16 | S 15
1967

from which

A fir, 20 ins. diam., bears N. $60\frac{1}{2}^{\circ}$ E., $134\frac{1}{2}$ lks. dist., mkd. N $1/16$ S15 BT.

A fir, 21 ins. diam., bears N. 31° W., 101 lks. dist., mkd. N $1/16$ S16 BT.

Ascend 100 ft. over SE. slope.

20.00 Leave logged area, edge bears E. and W.; enter heavy timber.

26.00 Ridge divide bet. Jerry Creek and Lane Creek, bears NW. and SE.; asc. 130 ft. along E. slope.

39.78 Point for the cor. of secs. 9, 10, 15, and 16 at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 6 W
S 9 | S 10
S 16 | S 15
1967

from which

A white fir, 7 ins. diam., bears N. $26\frac{1}{2}^{\circ}$ E., 64 lks. dist., mkd. T30S R6W S10 BT.

A fir, 20 ins. diam., bears S. 75° E., $18\frac{1}{2}$ lks. dist., mkd. T30S R6W S15 BT.

A fir, 25 ins. diam., bears S. $63\frac{1}{2}^{\circ}$ W., 36 lks. dist., mkd. T30S R6W S16 BT.

A fir, 22 ins. diam., bears N. 63° W., 46 lks. dist., mkd. T30S. R6W S9 BT.