

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 30 S., R. 6 W.

## CHAINS

From this point a locally established cor. of which I have no record, bears S.  $80^{\circ}$  W., 0.31 chs. dist., monumented with an iron bolt, 1 in. diam., protruding 10 ins. above ground, firmly set from which local bearing trees:

A shattered fir, 18 ins. diam., bears N.  $75^{\circ}$  E., 4 lks. dist., with scribe marks S10 visible on opened blaze.

A madrone, 12 ins. Diam., bears S.  $55\frac{1}{4}^{\circ}$  E.,  $32\frac{1}{2}$  lks. dist., with scribe marks S15 BT visible on open blaze.

A shattered fir, 15 ins. diam., bears S.  $43\frac{1}{4}^{\circ}$  W., 30 lks. dist., with illegible scribe marks visible on opened blaze.

A stump hole, bears N.  $72^{\circ}$  W., 14 lks. dist., alongside of which is an uprooted fir, 16 ins. diam., with a healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, madrone, oak, and cedar; undergrowth, fern, salal, poison oak, vine maple, and wild currant.

From the cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1964, monumented with an iron post, 1 in. diam., protruding 14 ins. above ground, firmly set, with brass cap mkd.

## COUNTY SURVEYORS OFFICE

T 30 S  
 S 10 | S 11  
 S 15 | S 14  
 R 6 W  
 1964

from which the remaining original bearing tree

A sawed and rotted oak stump, 28 ins. diam., bears N.  $48^{\circ}$  E., 254 lks. dist., with scribe marks BT visible in negative on overgrowth inside hollow trunk which is lying alongside. (Record bearing, N.  $50^{\circ}$  E.)

and bearing trees mkd. by Byron in 1964.

A madrone, 5 ins. diam., bears N.  $55\frac{3}{4}^{\circ}$  E., 45 lks. dist., with scribe marks S11 CS BT visible on open blaze.

A madrone, 10 ins. diam., bears S.  $8\frac{1}{2}^{\circ}$  E.,  $79\frac{1}{2}$  lks. dist., with scribe marks T30S R6W CS S14 BT visible on open blaze.

A madrone, 5 ins. diam., bears S.  $25\frac{1}{2}^{\circ}$  W., 82 lks. dist., with scribe marks S15 CS BT visible on open blaze.

A fir, 7 ins. diam., bears N.  $76\frac{1}{2}^{\circ}$  W.,  $98\frac{1}{2}$  lks. dist., with a healed blaze.

N  $89^{\circ} 47'$  W., bet. secs. 10 and 15.

Ascend 410 ft. over SE. slope, across partially logged area, through scattering timber and moderate undergrowth.