

County Surveyor's Record, Douglas County, Oregon

14343

Dependent Resurvey, Portion Subdivisional Lines, T. 30 S., R. 6 W.

CHAINS

- 3.30 Wire fence, bears N. 20° W. and S. 20° E.
- 13.55 Dirt road, 15 lks. wide, bears N. 60° E. and S. 70° W.
- 16.00 Same road, bears S. 70° E. and NW. curving to W.
- 26.50 Spur, slopes S.; desc. 90 ft. over W. slope.
- 31.50 Ravine, drains S. 40° W.; desc. 20 ft. along S. slope.
- 35.00 Creek, 2 lks. wide, course S. 70° W.; asc. 15 ft. along S. slope.
- 40.18 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

T 30 S R 6 W
 $\frac{1}{4}$ $\frac{S 10}{S 15}$
 1967

from which

A fir, 31 ins. diam., bears N. 80 $\frac{3}{4}$ ° E., 71 lks. dist., mkd. $\frac{1}{4}$ S10 BT.

A fir, 35 ins. diam., bears, S. 44° W., 40 lks. dist., mkd. $\frac{1}{4}$ S15 BT.

Ascend 15 ft. along S. slope.
- 41.00 Wire fence, bears N. and S.
- 43.00 Top of ascent, slopes S.; desc. 110 ft. along broken S. slope.
- 52.50 Creek, 2 lks. wide, course S. 10° W.; desc. 155 ft. over SW. slope.
- 60.27 Point for the W $\frac{1}{16}$ sec. cor. of secs. 10 and 15.
Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

W $\frac{1}{16}$ $\frac{S 10}{S 15}$
 1967

from which

A fir, 28 ins. diam., bears N. 39 $\frac{1}{2}$ ° W., 138 $\frac{1}{2}$ lks. dist., mkd. W $\frac{1}{16}$ S10 BT.

A fir, 18 ins. diam., bears S. 21 $\frac{1}{4}$ ° W., 72 $\frac{1}{2}$ lks. dist., mkd. W $\frac{1}{16}$ S15 BT.

Descend 4 ft. over SW. slope.
- 61.10 Lane Creek, 4 lks. wide, course S. 35° E.; also leave logged area, edge bears N. and S.; asc. 680 ft. over steep E. slope, through heavy timber,
- 74.50 Dirt road, 15 lks. wide, bears NE. curving to N. and SW. curving to S.
- 80.36 The cor. of secs. 9, 10, 15, and 16.