

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 30 S., R 6 W.

CHAINS

A dead madrone, 25 ins. diam., bears S.  $1\frac{1}{4}^{\circ}$  W.,  $22\frac{1}{2}$  lks. dist., with no scribe marks visible on opened blaze.

and a bearing tree mkd. by Markham in 1952,

A shattered fir, 10 ins. diam., bears N.  $40\frac{1}{2}^{\circ}$  W., 36 lks. dist. with scribe marks  $\frac{1}{4}$  S4 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground directly over the local iron pipe, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 4\ | \ S\ 3 \\ T\ 30\ S\ R\ 6\ W \\ 1967 \end{array}$$

from which a new bearing tree

A fir, 30 ins. diam., bears N.  $85^{\circ}$  E., 15 lks. dist., mkd.  $\frac{1}{4}$  S4 BT.

N.  $5^{\circ} 02'$  E., beginning new measurement.

Descend 9 ft. over NE. slope.

- 0.50 Spring branch, 1 lk. wide, course E.; asc. 290 ft. over SE slope.
- 18.80 Gravelled road, 15 lks. wide, bears NE. and W. curving to SW.
- 30.70 Main ridge of Boomer Hill, bears NE. and SW.; also another gravelled road, 15 lks. wide, bears N.  $35^{\circ}$  E. and SW.; desc. 65 ft. over N. slope.
- 36.53 The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., rehabilitated by Hans W. Thielsen and C. Albert White, in 1958, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., protruding 6 ins. above the ground, firmly set, with brass cap mkd.

$$\begin{array}{c} T\ 29\ S\ R\ 6\ W \\ S\ 33\ | \ S\ 34 \\ \hline S\ 4\ | \ S\ 3 \\ T\ 30\ S \\ 1958 \end{array}$$

from which the bearing trees described by Thielsen and White in 1968

A shattered white fir, 30 ins. diam., bears N.  $62^{\circ}$  E.,  $130\frac{1}{2}$  lks. dist., with scribe marks T29S R6W S34 CS BT visible on open blaze.

A white fir, 18 ins. diam., bears S.  $57^{\circ}$  E., 59 lks. dist., with a healed blaze.

A white fir snag, 40 ins. diam., bears S.  $9^{\circ}$  E., 21 lks. dist., with scribe marks T30S R6W S3 BT visible on opened blaze.

A white fir, 17 ins. diam., bears N.  $20\frac{1}{2}^{\circ}$  W.,  $93\frac{1}{2}$  lks. dist., with scribe marks T29S R6W S33 CS BT visible on open blaze.