

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 30 S., R. 6 W.

CHAINS

N. 1° 19' E., bet. secs. 4 and 5.

Descend 3 ft. over NE. slope, across open barren.

1.00 Leave barren, edge bears NE. and SW.; enter partially logged area covered with scattering timber and moderate undergrowth.

1.50 Main ridge of Nickel Mountain, bears N. 35° E., and S. 35° W.; desc. 205 ft. over NW. slope.

14.50 Spur, slopes NW.; desc. 205 ft. over NE. slope.

16.10 Gravelled road, 15 lks. wide, bears N. 80° E. and S. 80° W.

25.35 Gravelled road, 15 lks. wide, bears E. curving to NE. and W. curving to SW.

28.10 Bottom of descent, slopes NW.; asc. 115 ft. over SW. slope.

37.00 Gravelled road, 20 lks. wide, bears E. curving to SE. and W. curving to NW.

39.00 Spur, slopes SW.; desc. 3 ft. over NW. slope.

40.16 The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1957, from the original bearing trees, monumented with an iron bar, $1\frac{1}{2}$ x $3\frac{1}{2}$ ins. cross section, protruding 10 ins. above ground, firmly set, in a mound of stone, 2 ft. base, 6 ins. high, from which the remaining original bearing tree:

A stump hole, bears S. 7° E., 45 lks. dist., with fallen and rotted oak alongside, 30 ins. diam., with scribe marks $\frac{1}{4}$ S visible on opened and rotted blaze.

and bearing trees mkd. by Markham in 1957.

A white oak, 10 ins. diam., bears S. 74° E., 95 lks. dist., with scribe marks $\frac{1}{4}$ S4 T30S BT visible on open blaze.

A white oak, 7 ins. diam., bears S. 5 $\frac{3}{4}$ ° W., 85 $\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S5 X visible on open blaze.

A fir snag, 12 ins. diam., bears S. 84 $\frac{3}{4}$ ° W., 33 $\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S5 BT visible on open blaze.

and a bearing tree mkd. by J. W. Byron, Deputy County Surveyor, in 1962,

A cedar, 12 ins. diam., bears N. 47 $\frac{1}{2}$ ° E., 104 lks. dist., with scribe marks $\frac{1}{4}$ S4 CS BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 6 W

$$\begin{array}{c} \frac{1}{4} \\ S 5 | S 4 \\ 1967 \end{array}$$

Deposit the iron bar alongside the iron post.