

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 31 S., R. 5 W.

CHAINS

A root hole, bears N. 55° W., 21 lks. dist., alongside of which is a fallen madrone, 10 ins. diam., with illegible scribe marks visible on opened and rotted blaze.

A fir, 36 ins. diam., bears S. 30° E., 50 lks. dist., with old axe marks visible.

and bearing trees mkd. by Byron in 1963,

A fir, 7 ins. diam., bears N. 25° W., 26 lks. dist., with a healed blaze.

A fir, 10 ins. diam., bears S. 35° W., 25 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground directly over the iron rod, with brass cap mkd.

$\frac{1}{4}$ S 1
 T 31 S R 5 W
 1967

S 89° 52' W., beginning new measurement.

Ascend 40 ft. over NE. slope.

1.01 Point for the $\frac{1}{4}$ sec. cor. of sec. 36 only, on the S. bdy. of T. 30 S., R. 5 W., at proportionate distance, based on the 1854 Ford record. There is no remaining evidence of the original corner. No permanent monument established.

Ascend 25 ft. over NE. slope.

1.90 Spur, slopes N. 10° W.; desc. 440 ft. over NW. slope.

13.00 Creek, 1 lk. wide, course N.; asc. 480 ft. over NE. slope.

29.90 Ravine, drains NE.; asc. 310 ft. over NE. slope.

38.48 The cor. of secs. 1 and 2 only, on the N. bdy. of the Tp., established by Byars in 1882, perpetuated and recorded by V. S. King, Registered Land Surveyor No. 442, in 1959, again perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 in. diam., protruding 16 ins. above ground, firmly set, with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R5W S35 S36 S1 S2 T31S 1963, from which the remaining original bearing trees:

A fir snag, 19 ins. diam., bears N. 40° E., 26 lks. dist., with a healed blaze. Remarkd RS 442 S36 T30S R5W BT on the bark by King in 1959.

A fir, 45 ins. diam., bears S. 20° W., 52 lks. dist., with illegible scribe marks visible on bark blaze. Remarkd S2 T31S R5W BT on the bark by King in 1959. (Record, 56 lks.)

A dogwood clump, bears N. 28° W., 15 lks. dist.

and bearing trees mkd. by King in 1959,

A fir, 38 ins. diam., bears S. 51° E., 55 lks. dist., with scribe marks RS 442 S1 T31S R5W BT visible on a bark blaze.