

Dependent Resurvey, Portion of N. Bdy., T. 31 S., R. 5 W.

CHAINS

A dogwood, 5 ins. diam., bears N. 15° W., 11 lks. dist., with scribe marks S35 T30S R5W BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 5 W
S 36
S 2 | S 1
T 31 S R 5 W
1967

Reset the local iron post inverted alongside the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, oak, madrone, dogwood yew, maple, alder, cedar, pine, chinquapin, and willow; undergrowth, salal, fern, poison oak, vine maple, hazel, arrowwood, wild rose, blackberry, Oregon grape, and reproduction.

N 89° 46' W., along the N. bdy. of sec. 2.

Ascend 50 ft. over NE. slope across partially logged area, through scattering timber and dense undergrowth.

1.20 Point for the cor. of secs. 35 and 36 only, on the S bdy. of T. 30 S., R. 5 W., at proportionate distance, based on the 1854 Ford record. There is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 5 W
S 35 | S 36
S 2
T 31 S R 5 W
1967

from which

A fir, 40 ins. diam., bears N. 7¼° E., 100 lks. dist., mkd. T30S R5W S36 BT.

A fir, 8 ins. diam., bears N. 39¼° W., 149 lks. dist., mkd. T30S R5W S35 BT.

Ascend 75 ft. over NE. slope.

3.00 Ridge dividing O'Shea Creek and Canyon Creek drainage, bears N. 30° W. and S. 30° E.; also underground gas pipe line, bears the same; desc. 340 ft. along S. slope changing to SW. slope.

13.70 Ravine, drains S. 30° W.; asc. 15 ft. over SE. slope.

15.70 Top of ascent, slopes SW.; desc. 25 ft. over SE. slope.

19.325 Point for the E 1/16 sec. cor. of sec. 2 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 S 2
1967

from which