

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 31 S., R. 5 W.

## CHAINS

	Descend 5 ft. over W. slope.
1.60	Creek, 2 lks. wide, course SW.; asc. 130 ft. over broken SE. slope.
13.00	Spur, slopes S.; also dirt road, 12 lks. wide, bears N. 10° E. and S. 10 W.; desc. 150 ft. over SW. slope.
15.07	From this point, United States Coast and Geodetic Survey triangulation station GAS, 1963, bears North, 0.695 chs. dist., monumented with a concrete post, 8 ins. sq., protruding 4 ins. above ground, firmly set, with brass tablet, .2 ins. diam., set in top, mkd. OREGON STATE HIGHWAY DEPT. Elev. GAS Station USC & GS 1963.
16.90	High voltage transmission line, bears N. 30° W. and S. 60° E.
18.90	Another high voltage transmission line, bears N. 30° W. and S. 30° E. turning to SE.
19.20	Point for the W 1/16 sec. cor. of sec. 2 only.  Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, supported in a mound of stone, 5 ft. base, to top, with brass cap mkd.  $\frac{W\ 1/16\ S\ 2}{1967}$ from which  A fir, 28 ins. diam., bears S. 4½° E., 285 lks. dist., mkd. W 1/16 S2 BT.  A fir, 28 ins. diam., bears S. 24½° W., 252 lks. dist., mkd. W 1/16 S2 BT.  Descend 455 ft. over W. slope changing to NW. slope.
26.35	Power line, bears N. 30° W. and S. 40° E.
29.70	Telephone line, bears N. and SE.
30.40	Wire fence at E. edge of highway right of way, bears N. 25° W. and S. 70° E.
33.80	Center of N. bound lanes of Interstate Highway No. 5, 50 lks. wide, bears N. 25° W. and S. 25° E.
34.00	Canyon Creek, 35 lks. wide, about 30 ft. underneath freeway, course NE. curving to N.; asc. 85 ft. over E. slope.
34.60	Center of S. bound lanes of Interstate Highway No. 5, 50 lks. wide, bears N. 25° W. and S. 25° E.
38.00	Wire fence at W. edge of highway right of way, bears N. 30° W. and S. 30° E.; enter timber.
38.40	The cor. of secs. 2 and 3 only, on the N. bdy. of the Tp., established by Byars in 1882, perpetuated and recorded by V. S. King, Registered Land Surveyor No. 442, in 1959, again perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 in. diam., protruding 16 ins. above ground, firmly set, with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R5W S34 S35 S3 S2 T31S 1963, from which the original bearing trees:  A fir, 27 ins. diam., bears N. 14° E., 64 lks. dist., with illegible scribe marks visible on bark blaze. Remarked S35 T30S R5 W BT on the bark by King in 1959. (Record, N. 12° E.)