

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., $\frac{1}{4}$ 31 S., R. 5 W.

CHAINS

A fir, 18 ins. diam., bears S. 54° E., 65 lks. dist., with no marks visible. Remarkd S2 T31S R5W BT on the bark by King in 1959. (Record, 72 lks.)

A root hole, bears S. 28° W., 9 lks. dist., alongside of which is a fallen live oak, 18 ins. diam., with illegible scribe marks visible on rotted blaze.

A fir, 30 ins. diam., bears N. 26° W., 16 lks. dist., with illegible scribe marks visible on bark blaze. Remarkd S34 T30S R5W BT on the bark by King in 1959. (Record, 14 lks.)

and a bearing tree mkd. by King in 1959.

A fir, 10 ins. diam., bears S. $21\frac{1}{2}^{\circ}$ W., 47 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

T 30 S R 5 W
S 35
S 3 S 2
T 31 S R 5 W
1967

Deposit local iron post inverted alongside the iron post.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

Timber, fir, oak, madrone, dogwood, maple, pine, and cedar; undergrowth, poison oak, salal, fern Oregon grape, hazel, arrowwood, vine maple, Scotch broom, and reproduction.

N. $89^{\circ} 42'$ W., along the N. bdy. of sec. 3.

Ascend 65 ft. over E. slope, through heavy timber and dense undergrowth.

1.49

Point for the cor. of secs. 34 and 35 only, on the S. bdy. of T. 30 S., R. 5 W., established by extending the line bet. secs. 34 and 35 through the original 1854 Ford cor. of secs. 2, 3, 34, and 35 to an intersection with the 1882 Byars township line.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 5 W
S 34 S 35
S 3
T 31 S R 5 W
1967

from which

A fir, 20 ins. diam., bears N. $20\frac{1}{4}^{\circ}$ E., 23 lks. dist., mkd. T30S R5W S35 BT.

A fir, 18 ins. diam., bears N. $57\frac{1}{2}^{\circ}$ W., 37 lks. dist., mkd. T30S R5W S34BT.

From this point the original 1854 Ford cor. of secs. 2, 3, 34, and 35, bears N. $0^{\circ} 57'$ E., 5.58 chs. dist., monumented with an iron pipe, 1 in. diam., protruding 6 ins. above ground, firmly set, witnessed as described in the official record of a 1967 resurvey, under Group 614, Oregon.