

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 31 S., R. 5 W.

## CHAINS

- 16.00 Bottom of descent, drains N.; asc 235 ft. over NE. slope.
- 26.00 Spur ridge, bears N. 30° W., and S. 30° E.; desc. 710 ft. over steep SW. slope.
- 27.00 Leave timber, edge bears NW. and SW.; enter rocky barren.
- 40.00 Leave barren, edge bears NE. and SE.; enter heavy timber and dense undergrowth.
- 45.00 Creek, 2 lks. wide, course N. 20° W.; asc. 45 ft. over NE. slope.
- 47.02 Point for the cor. of secs. 33 and 34 only, on the S. bdy. of T. 30 S., R. 5 W., at proportionate distance, based on the 1854 Ford record. There is no remaining evidence of the original corner. No permanent monument established.
- Descend 35 ft. over NW. slope.
- 48.355 The cor. of secs. 3 and 4 only, on the N. bdy. of the Tp., established by Wright in 1878 as a closing cor. for secs. 3 and 4, adopted by Byars in 1882 as a cor. of maximum control, perpetuated and recorded by B. B. Irving, Deputy County Surveyor, in 1930, monumented with a washed boulder, 36 x 12 x 10 ins., firmly set 20 ins. in the ground, mkd. with 4 notches on E. and 6 notches on S. edge, from which the remaining bearing trees mkd. by Wright:
- A fir, 44 ins. diam., bears S. 38° W., 20 lks. dist.,  
with illegible scribe marks visible on opened blaze.
- A fir stump, 12 ins. diam., bears N. 83° W., 18 lks. dist.,  
with no marks remaining.
- and bearing trees mkd. by Irving in 1930,
- A fir, 27 ins. diam., bears S. 89° E., 44 lks. dist., with  
scribe marks S3 T31S R5W CC CS BT visible on double  
bark blaze.
- A fir, 30 ins. diam., bears S. 35° W., 52 lks. dist.,  
with scribe marks S4 T31S R5W CC CS BT visible on  
double bark blaze.
- and a bearing tree mkd. by J. W. Byron, Deputy County Surveyor,  
in 1959,
- A fir, 15 ins. diam., bears N. 87° W., 26 lks. dist.,  
with a healed blaze.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground  
with brass cap mkd.
- T 30 S R 5 W

S 33

---

S 4 | S 3

T 31 S R 5 W

1967
- Deposit the corner stone alongside the iron post.