

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bsy, T. 31 S., R. 5 W.

CHAINS

55.80 Alder Creek, 2 lks. wide, course N. 15° W.; asc. 290 ft. over NE. slope.

61.44 Point for the W 1/16 Sec. cor. of sec. 4 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{W } 1/16 \text{ S } 4 \\ 1967 \end{array}$$

from which

A fir, 8 ins. diam., bears S. 55° E., 46½ lks. dist., mkd. W 1/16 S4 BT.

A fir, 6 ins. diam., bears S. 70½° W., 36 lks. dist., mkd. W 1/16 S4 BT.

Ascend 70 ft. over NE. slope.

63.60 Top of ascent, slopes NE.; continue along broken N. slope.

69.80 Ravine, drains N. 50° E.; asc. 185 ft. over E. slope.

74.67 Intersect claim line 1-2, Skookum Lode, Mineral Survey NO. 794.

Point for the closing corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

$$\begin{array}{c} \text{T } 30 \text{ S } \text{R } 5 \text{ W} \\ \text{C } 794 \text{ } \begin{array}{c} \text{S } 33 \\ \text{S } 4 \end{array} \text{ CC} \\ \text{T } 31 \text{ S} \\ 1968 \end{array}$$

from which

A fir, 7 ins. diam., bears N. 35½° E., 175½ lks. dist., mkd. T30S R5W S33 CC BT.

A fir, 29 ins. diam., bears S. 50° E., 141 lks. dist., mkd. T31S R5W S4 CC BT.

From this point, Cor. No. 1, Skookum Lode, Mineral Survey No. 794, bears N. 25° 55' W., 1.48 chs. dist., herein-after described.

Ascend 20 ft. over E. slope.

76.00 Spur, slopes NE.; asc. 50 ft. along N. slope.

78.07 Intersect claim line 1-4, Skookum Lode, Mineral Survey No. 794.

Point for the closing corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.

$$\begin{array}{c} \text{T } 30 \text{ S } \text{R } 5 \text{ W} \\ \text{CC } \begin{array}{c} \text{S } 33 \\ \text{S } 4 \end{array} \text{ C } 794 \\ \text{T } 31 \text{ S} \\ 1968 \end{array}$$

from which