

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 31 S., R. 5 W.

CHAINS

A fir, 16 ins. diam., bears N. 86° W., 112 lks. dist.,
with illegible scribe marks visible on open blaze.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

Timber, fir, madrone, pine, cedar, oak, yew, chinquapin, maple, and
alder; undergrowth, salal, fern, poison oak, hazel, arrowwood,
vine maple, Oregon grape, and reproduction.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 5 W., Willamette Meridian, Oregon

(Restoring the 1878 survey by William P. Wright and the 1882
survey by William H. Byars.)

From the cor. of secs. 3, 4, 9, and 10, monumented with the original
mound of stone, 3 ft. base, 1 ft. high, perpetuated and recorded by
B. B. Irving, Deputy County Surveyor, in 1930, again perpetuated
and recorded by J. H. Markham, Jr., Registered Engineer No. 2880,
in 1957, monumented with an iron rod, 20 ins. long, $\frac{1}{2}$ in. diam.
firmly set 10 ins. in the ground and in center of original mound of
stone, from which bearing trees mkd. by Irving in 1930:

A fir, 34 ins. diam., bears S. 72° W., 58 lks. dist.,
with illegible scribe marks visible on bark. Remarkd
T31S R5W S9 BT on double blaze by the County Surveyor
in 1966.

A fir, 25 ins. diam., bears N. 29° W., 59 lks. dist., with
illegible scribe marks visible on bark. Remarkd T31S
R5W S4 CS BT on double blaze by the County Surveyor in
1966.

and bearing trees mkd. by the County Surveyor in 1966,

A fir, 6 ins. diam., bears N. 20° E., 72 lks. dist., with
scribe marks T31S R5W S3 CS BT visible on open double
blaze.

A live oak, 6 ins. diam., bears S. 68° E., 44 lks. dist.,
with scribe marks T31S R5W S10 CS BT visible on open
double blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the
ground, and in a mound of stone, 3 ft. base, to top, with brass cap
mkd.

T 31 S R 5 W
S 4 S 3
S 9 S 10
1966

Deposit the iron rod alongside the iron post.