

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS

N. $0^{\circ} 01'$ W., bet. secs. 3 and 4, marking and blazing the true line.

Ascend 275 ft. over SW slope changing to S. slope along spur, through heavy timber and dense undergrowth.

13.85 Leave timber and undergrowth, edge bears E. and W.; enter barren.

17.50 Ridge, bears E. and W.; also leave barren, edge bears the same; desc. 65 ft. over NW. slope, through timber and undergrowth.

20.40 Point for the S $1/16$ sec. cor. of secs. 3 and 4.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S $1/16$
S $4 \frac{1}{4}$ S 3
1966

from which

A fir, 30 ins. diam., bears S. 52° E., 44 lks. dist., mkd. S $1/16$ S3 BT.A fir, 35 ins. diam., bears N. $45\frac{1}{2}^{\circ}$ W., $12\frac{1}{2}$ lks. dist., mkd. S $1/16$ S4 BT.

Descend 510 ft. over broken NW. slope.

40.80 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 31 S R 5 W
 $\frac{1}{4}$
S $4 \frac{1}{4}$ S 3
1966

from which

A fir, 11 ins. diam., bears S. $86\frac{1}{2}^{\circ}$ E., 145 lks. dist., mkd. $\frac{1}{4}$ S3 BT.A fir, 15 ins. diam., bears N. $53\frac{1}{2}^{\circ}$ W., 148 lks. dist., mkd. $\frac{1}{4}$ S4 BT.

Descend 630 ft. over NW. slope.

61.20 Point for the N $1/16$ sec. cor. of secs. 3 and 4.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

N $1/16$
S $4 \frac{1}{4}$ S 3
1966

from which

A fir, 9 ins. diam., bears S. $13\frac{1}{2}^{\circ}$ E., 70 lks. dist., mkd. N $1/16$ S3 BT.A fir, 17 ins. diam., bears N. 53° W., $19\frac{1}{2}$ lks. dist., mkd. N $1/16$ S4 BT.