

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS																									
81.60	<p>Descend 745 ft. over NW. slope.</p> <p>The cor. of secs. 3 and 4 only, on the N. bdy. of the Tp.</p> <p>Land, mountainous. Soil, rocky clay with rock outcroppings. Timber, fir, oak, madrone, cedar, pine, yew, and dogwood; undergrowth, fern, salal, vine maple, poison oak, Oregon grape, hazel, arrowwood, and reproduction.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17, perpetuated and recorded by V. S. King, Registered Land Surveyor No. 442, in 1959, monumented with an iron pipe, 36 ins. long, 1 in. diam., firmly set 30 ins. in the ground, from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A dogwood stump, 8 ins. diam., bears S. 21° E., 13 lks. dist., with no marks remaining.</p> <p>and bearing trees mkd. by King in 1959,</p> <p style="padding-left: 40px;">A white fir, 25 ins. diam., bears N. 69½° E., 13 lks. dist., with scribe marks S9 T31S R5W BT visible on open blaze.</p> <p style="padding-left: 40px;">A white fir, 20 ins. diam., bears S. 64½° E., 129 lks. dist. with a healed blaze.</p> <p style="padding-left: 40px;">A white fir, 12 ins. diam., bears S. 41½° W., 16 lks. dist., with scribe marks S17 T31S R5W BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 56 ins. diam., bears N. 29° W., 58½ lks. dist., with scribe marks RS 442 S8 T31S visible on bark. Remarked T31S R5W S8 CS BT by County Surveyor in 1966.</p> <p>and a bearing tree mkd. by the County Surveyor in 1966,</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 85° W., 85 lks. dist., with scribe marks T31S R5W S9 CS BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T</td> <td style="padding: 0 5px;">31</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">R</td> <td style="padding: 0 5px;">5</td> <td style="padding: 0 5px;">W</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S</td> <td style="padding: 0 5px;">8</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S</td> <td style="padding: 0 5px;">9</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S</td> <td style="padding: 0 5px;">17</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S</td> <td style="padding: 0 5px;">16</td> <td></td> </tr> <tr> <td></td> <td colspan="4" style="padding: 0 5px;">1966</td> <td></td> </tr> </table> </div> <p style="padding-left: 40px;">Deposit the iron pipe alongside the iron post.</p> <p>N. 2° 56' W., bet. secs. 8 and 9.</p> <p>Descend 200 ft. over broken NE. slope, through heavy timber and dense undergrowth.</p>	T	31	S	R	5	W		S	8	S	9			S	17	S	16			1966				
T	31	S	R	5	W																				
	S	8	S	9																					
	S	17	S	16																					
	1966																								
8.20	<p>Creek, 1 lk. wide, course S. 85° E.; asc. 520 ft. over broken SW. slope.</p>																								
41.57	<p>Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p>																								