

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 5 W
 $\frac{1}{4}$
 S 8 | S 9
 1966

from which

A fir, 14 ins. diam., bears S. 67° E., 17 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

A fir, 25 ins. diam., bears N. 47° W., $51\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Ascend 150 ft. over SW. slope.

55.00 Creek, 1 lk. wide, course S. 30° W.; asc. 875 ft. over steep SE. slope changing to S. slope.

80.20 Record distance for witness cor. for cor. secs. 4, 5, 8, and 9; there is no remaining evidence of the original corner.

82.80 Main ridge of Tellurium Peak, bears N. 80° E., and S. 80° W.; also enter logged area, edge bears the same; desc. 8 ft. over N. slope.

83.14 Point for the cor. of secs. 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original witness corners.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 31 S R 5 W
 $\frac{1}{4}$
 S 5 | S 4
 S 8 | S 9
 1966

from which

A white fir, 12 ins. diam., bears N. 83° E., $87\frac{1}{2}$ lks. dist., mkd. T31S R5W S4 BT.

A cedar, 17 ins. diam., bears S. $76\frac{1}{2}^\circ$ E., 295 lks. dist., mkd. T31S R5W S9 BT.

A fir, 10 ins. diam., bears S. 46° W., 26 lks. dist., mkd. T31S R5W S8 BT.

A fir, 25 ins. diam., bears N. 61° W., 212 lks. dist., mkd. T31S R5W S5 BT.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

Timber, fir, pine, oak, cedar, yew, madrone, chinquapin, dogwood, and alder; undergrowth, salal, fern, poison oak, Oregon grape, ceanothus, huckleberry, blackberry, wild rose, and reproduction.

From the cor. of secs. 3, 4, 9, and 10.

S. $89^\circ 15'$ W., bet. secs. 4 and 9.

Descend 400 ft. over SW. slope, through heavy timber and dense undergrowth.

13.60 Bottom of descent, drains S.; asc. 70 ft. over SE. slope.