

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 31 S., R. 5 W.

## CHAINS

- 21.28 Point for the W. 1/16 sec. cor. of secs. 4 and 9.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- W 1/16  $\frac{S 4}{S 9}$   
1966
- from which
- A fir, 20 ins. diam., bears N. 27° E., 27 lks. dist., mkd. W 1/16 S4 BT.
- A fir, 11 ins. diam., bears S. 57° W., 10 lks. dist., mkd. W 1/16 S9 BT.
- Ascend 60 ft. over SE. slope.
- 24.20 Spur, slopes S.; desc. 75 ft. over SW. slope.
- 28.10 Same dirt road, 15 lks. wide, bears N. 7° W. curving to W. and S. 7° E. curving to E.; also enter timber, edge bears the same.
- 29.70 Bottom of descent, drains S.; asc. 30 ft. over SE. slope.
- 40.60 Ridge, bears N. 80° E. and S. 80° W.; also enter logged area, edge bears the same; thence along N. slope.
- 42.56 The cor. of secs. 4, 5, 8, and 9.  
Land, mountainous.  
Soil, rocky clay with rock outcroppings.  
Timber, fir, pine, oak, cedar, hemlock, yew, madrone, chinquapin, dogwood, and alder; undergrowth, manzanita, poison oak, ceanothus, huckleberry, blackberry, fern, salal, Oregon grape, and reproduction.
- 
- N. 3° 00' E., bet. secs. 4 and 5.  
Descend 735 ft. over steep N. slope, through heavy timber and dense undergrowth.
- 2.20 Dirt road, 10 lks. wide, bears N. 75° W. and S. 65° E.
- 9.00 Record distance for witness cor. for secs. 4, 5, 8, and 9; there is no remaining evidence of the original corner.
- 18.60 Dirt road, 10 lks. wide, bears NE. and SW.
- 20.79 Point for the S 1/16 sec. cor. of secs. 4 and 5.  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- S 1/16  
S 5 | S 4  
1966
- Fd. BC + 2 BTs by  
R. Quimby 6/2016  
M171-12 A+B
- from which
- A hemlock, 7 ins. diam., bears N. 52° E., 21 lks. dist., mkd. S 1/16 S4 BT.
- A hemlock, 10 ins. diam., bears S. 34° W., 39 lks. dist., mkd. S 1/16 S5 BT.
- Descend 70 ft. over N. slope.