

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 31 S., R 5 W.

CHAINS

23.50

Creek, 1 lk. wide, course NE.; asc. 75 ft. over SE. slope.

31.185

Point for the N-S 1/64 sec. cor. of secs. 4 and 5.

Set an iron post, 28 ins. long 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

N-S
1/64
S 5 | S 4
1966

Fd. BC + 2 BTs by
R. Quimby 6/2016
M171-12 A+B

from which

A hemlock, 8 ins. diam., bears S. 38° E., 16½ lks. dist.,
mkd. N-S 1/64 S4 BT.

A fir, 7 ins. diam., bears S. 42° W., 33 lks. dist., mkd.
N-S 1/64 S5 BT.

Descend 115 ft. over NE. slope.

41.58

The ¼ sec. cor. of secs. 4 and 5, perpetuated and recorded by G. J. Wenderoth, Deputy County Surveyor, in 1958, monumented with an iron pipe, 1 in. diam., protruding 12 ins. above ground, firmly set, from which the remaining original bearing tree:

A fir, 22 ins. diam., bears N. 26° W., 12 lks. dist., with
a healed blaze.

and a bearing tree reported by Wenderoth,

A cedar, 50 ins. diam., bears S. 65° W., 57 lks. dist.,
with scribe mark B visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ Ins. diam., 22 ins. in the ground, with brass cap mkd.

T 31 S R 5 W
¼
S 5 | S 4
1966

from which a new bearing tree

A hemlock, 13 ins. diam., bears S. 55½° E., 32 lks. dist.,
mkd. ¼ S4 BT.

Deposit the iron pipe alongside the iron post.

N 1° 24' E., beginning new measurement.

Ascend 8 ft. along E. slope.

8.30

Top of ascent, slopes E.; desc. 9 ft. over NE. slope.

10.405

Point for the S-N 1/64 sec. cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S-N
1/64
S 5 | S 4
1966

Fd. BC + 2 BTs by
R. Quimby 6/2016
M171-12 A+B

from which