

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS

Point for the closing corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

T 31 S R 5 W
CC
S 5 S 4

C 794
1968

Fd. BC + 2 BTs
 mkd 1 new BT
 R. Quimby 6/2016
 M171-12 A+B

from which

A fir, 30 ins. diam., bears N. 20° E., $43\frac{1}{2}$ lks. dist.,
 mkd. T31S R5W S4 CC BT.

A madrone, 6 ins. diam., bears S. 73° W., 82 lks. dist.,
 mkd. T31S R5W S5 CC BT.

From this point, Cor. No. 1, Mineral Survey No. 794, bears N. 64° 05'
 E., 7.40 chs. dist., hereinafter described.

Descend 60 ft. over NW. slope.

41.11

The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

Timber, fir, oak, madrone, cedar, pine, hemlock, yew, dogwood,
 chinquapin, and alder; undergrowth, manzanita, fern, salal, poison
 oak ceanothus, Oregon grape, huckleberry, blackberry, and
 reproduction.

From the cor. of secs. 17, 18, 19, and 20, perpetuated and recorded
 by V. S. King, Registered Land Surveyor, No. 442, in 1959, monumented
 with a steel rod, 1 in. diam., protruding 6 ins. above ground,
 firmly set, from which the remaining original bearing tree:

A fir, 38 ins. diam., bears N. 18° E., 33 lks. dist., with
 scribe mark B visible on opened blaze. Remarkd
 T31S R5W S17 BT RS 442 BT on bark, by King, in 1959.

and bearing trees mkd. by King in 1959,

A white fir, 9 ins. diam., bears S. 72° E., $19\frac{1}{2}$ lks. dist.,
 with illegible scribe marks visible on open blaze.

A white fir, 14 ins. diam., bears N. 40° W., 10 lks. dist.,
 with illegible scribe marks visible on open blaze.

and bearing trees mkd. by J. M. Powell, Deputy County Surveyor, in
 1966

A white fir, 8 ins. diam., bears N. 51° E., 63 lks. dist.,
 with scribe marks T31S R5W S17 CS BT visible on open
 blaze.

A white fir, 14 ins. diam., bears S. 83° W., $56\frac{1}{2}$ lks. dist.,
 with scribe marks T31S R5W S19 CS BT visible on open
 blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the
 ground, directly over the steel rod, with brass cap mkd.