

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS	
	<p>A fir, 24 ins. diam. bears N. 55° W., 43 lks. dist., mkd. S 1/16 S7 BT.</p> <p>Continue along W. slope.</p>
21.90	Spur, slopes N. 20° W.; desc. 585 ft. over NE. slope.
32.80	Leave timber, edge bears E. and W.; enter logged area.
41.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 14 ins in the ground to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 31 S R 5 W <math>\frac{1}{4}</math> S 7   S 8 1966</p> <p>from which</p> <p>A fir, 16 ins. diam., bears N. 16° E., 236 lks. dist., mkd. <math>\frac{1}{4}</math> S8 BT.</p> <p>A sawed fir stump, 11 ins. diam., bears N. 87<math>\frac{1}{2}</math>° W., 70 lks. dist., mkd. <math>\frac{1}{4}</math> S7 BT.</p> <p>Descend 530 ft. over broken NE. slope.</p>
59.50	Leave logged area, edge bears E. and W.; enter timber.
60.00	Spur, slopes N. 60° E.; desc. 50 ft. over NE. slope.
61.50	<p>Point for the N 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 7   S 8 1966</p> <p>from which</p> <p>A fir, 34 ins. diam., bears N. 25° E., 63 lks. dist., mkd. N 1/16 S8 BT.</p> <p>A fir, 43 ins. diam., bears S. 68° W., 57 lks. dist., mkd. N 1/16 S7 BT.</p> <p>Descend 390 ft. over NE. slope.</p>
70.20	Mitchell Creek, 4 lks. wide, course W.; asc. 180 ft. over SW. slope.
76.15	Dirt road, 15 lks. wide, bears N. 40° W. and S. 25° E.
82.00	<p>The cor. of secs. 5, 6, 7, and 8, occupied by the original corner tree, a fir, 33 ins. diam., with a healed blaze on the SE. and SW. face, from which the original bearing trees:</p> <p>A fir, 20 ins. diam., bears N. 30° E., 3 lks. dist., with a healed blaze.</p> <p>A pine, 26 ins. diam., bears S. 75° E., 24 lks. dist., with a healed blaze. (Record distance, 22 lks.)</p>