

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS

A madrone, 7 ins. diam., bears N. 16° W., 77 lks. dist.,  
mkd.  $\frac{1}{4}$  S5 BT.

A live oak, 5 ins. diam., bears S. 18 $\frac{1}{2}$ ° E., 43 $\frac{1}{2}$  lks. dist.  
mkd.  $\frac{1}{4}$  S8 BT.

N. 89° 24' W., beginning new measurement.

Descend 180 ft. over broken SW. slope.

21.28 Point for the W 1/16 sec. cor. of secs. 5 and 8.

Set an iron post, 28 ins. long 2 $\frac{1}{2}$  ins. diam., 24 ins. in the  
ground, with brass cap mkd.

W 1/16  $\frac{S 5}{S 8}$   
1966

from which

A pine, 9 ins. diam., bears N. 18° E., 69 lks. dist., mkd.  
W 1/16 S5 BT.

A madrone, 6 ins. diam., bears S. 40° W., 21 $\frac{1}{2}$  lks. dist.,  
mkd. W 1/16 S8 BT.

Descend 585 ft. over broken SW. slope.

42.56 The cor. of secs. 5, 6 7, and 8.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

Timber, fir, pine, oak, cedar, yew, madrone, chinquapin, dogwood,  
and alder; undergrowth, manzanita, poison oak, ceanothus, huckle-  
berry, blackberry, fern, salal, Oregon grape, and reproduction.

Dependent Resurvey, Skookum Lode, Mineral Survey No. 794,  
Willamette Meridian, Oregon

(Restoring the 1916 survey by H. C. Hall)

From Cor. No 1. Skookum Lode, monumented with the burned original  
cedar post, 5 ins. sq., 3 ft. long, lying on ground, with scribe  
marks 1-794 visible on one side, from which the original bearing  
tree:

A sawed and burned fir stump, 18 ins. diam., bears S 25°  
00' W., 3 $\frac{1}{2}$  lks. dist., with scribe marks SK visible on  
remaining portion of opened blaze. (Record, a pine)

At the corner point

Set an iron post, 28 ins. long 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground,  
with brass cap mkd.

T 30 S R 5 W

