

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 31 S., R 5 W.

CHAINS

from which a new bearing tree

A fir, 30 ins diam., bears S. 22° E., 153 lks. dist.,
mkd. 1-794 BT.

Deposit the wood post alongside the iron post.

S. 25° 55' E., on claim line 1-2, marking and blazing the tree line.

Ascend 5 ft. over N. slope, across logged and burned area, through
scattering timber and dense undergrowth.

0.90 Spur, slopes NE.; desc. 10 ft. along E. slope.

1.48 The closing cor. of secs. 4 and 33, on N. bdy. of T. 31 S., R. 5 W.
previously described.

Descend 60 ft. over SE. slope.

4.90 Bottom of descent, drains NE.; asc. 85 ft. over N. slope.

7.40 Spur, slopes NE.; desc. 10 ft. along E. slope.

9.09 Cor. No. 2, Skookum Lode, monumented with the burned original cedar
post, 5 ins. sq., protruding 3 ft. above the ground, firmly set,
from which the original bearing tree:

A burned madrone snag, 15 ins. diam., bears N. 81° 16' W.,
10 lks. dist., with scribe marks 2-794 SK visible on
opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd.

SK
2-794 S 4
T 31 S R 5 W
1968

from which a new bearing tree

A fir, 15 ins. diam., bears N. 57½° W., 195 lks. dist.,
mkd. 2-794 BT.

Deposit the wood post alongside the iron post.

S. 64° 05' W., on claim line 2-3, beginning new measurement.

Ascend 300 ft. over E. slope.

12.09 The closing cor. of secs. 4 and 5, T. 31 S., R. 5 W., previously
described.