

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Skookum Lode, Mineral Survey No. 794

CHAINS	
	<p>A fir, 42 ins. diam., bears N. $73\frac{1}{4}^{\circ}$ E., 428 lks. dist., mkd. 4-794 BT.</p> <p>N. $64^{\circ} 05'$ E., on claim line 1-4, beginning new measurement.</p> <p>Ascend 215 ft. over broken NW. slope.</p>
11.70	Spur, slopes NW.; desc. 35 ft. over N. slope.
15.33	The closing cor. of secs. 4, and 5, T. 31 S., R. 5 W., previously described.
	Ascend 5 ft. over NW. slope.
16.00	Spur, slopes N.; desc. 75 ft. over N. slope.
19.66	The closing cor. of secs. 4 and 33, on the N. bdy. of T. 31 S., R. 5 W., previously described.
	Descend 65 ft. over N. slope.
22.73	Cor. No. 1, Skookum Lode.
<p>Subdivision of Section 8, T. 31 S., R. 5 W. Willamette Meridian, Oregon</p>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.</p> <p>N. $4^{\circ} 47'$ W., on the N. and S. center line of sec. 8.</p> <p>Ascend 80 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
7.70	Spur, slopes N. 75° E.; desc. 135 ft. over NE. slope.
12.10	Ravine, drains N. 75° E.; asc. 55 ft. over SE. slope.
14.85	Spur, slopes E.; desc. 13 ft. over NE. slope.
16.65	Ravine, drains S. 60° E.; asc. 140 ft. over SE. slope.
20.71	Point for the center $\frac{1}{16}$ sec. cor. of sec. 8.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>C S $\frac{1}{16}$ S 8 C 1966</p>
	from which
	<p>A fir, 15 ins. diam., bears N. 72° E., $22\frac{1}{2}$ lks. dist., mkd. CS $\frac{1}{16}$ S8 BT.</p> <p>A madrone, 11 ins. diam., bears S. 88° W., 53 lks. dist., mkd. CS $\frac{1}{16}$ S8 BT.</p> <p>Ascend 360 ft. over SE. slope.</p>
41.42	Point for the center $\frac{1}{4}$ sec. cor. of sec. 8, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground with brass cap mkd.