

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 8, T. 31 S., R. 5 W.

CHAINS	
	T 31 S R 5 W C $\frac{1}{4}$ S 8 1966
	from which A fir, 30 ins. diam., bears N. 74° E., 83 lks. dist., mkd. C $\frac{1}{4}$ S 8 BT. A cedar, 28 ins. diam., bears S. 41° W., 173 lks. dist., mkd. C $\frac{1}{4}$ S 8 BT. Ascend 55 ft. over SE. slope.
45.40	Ridge dividing Canyon Creek and Mitchell Creek drainage, bears N. 35° E. and S. 35° W.; desc. 545 ft. over NW. slope.
62.43	Point for the center N 1/16 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} C \\ N\ 1/16\ S\ 8 \\ C \\ 1966 \end{array}$
	from which A fir, 20 ins. diam., bears N. 56° E., 53 $\frac{1}{2}$ lks. dist., mkd. CN 1/16 S 8 BT. A fir, 47 ins. diam., bears S. 78° W., 194 lks. dist., mkd. CN 1/16 S 8 BT. Descend 280 ft. over NW. slope
70.70	Creek, 1 lk. wide, course S. 70° W.; asc. 315 ft. over SE. slope.
83.44	The $\frac{1}{4}$ sec. cor. of secs. 5 and 8.
<hr/> From the $\frac{1}{4}$ sec. cor. of secs. 8 and 9. N 88° 09' W., on the E. and W. center line of sec. 8. Descend 125 ft. over SW. slope, through heavy timber and dense undergrowth.	
3.25	Creek, 1 lk. wide, course S.; asc. 580 ft. over SE. slope.
16.70	Spur, slopes S. 10° E.; desc. 220 ft. over SW. slope.
27.60	Creek, 1 lk. wide, course S.; asc. 430 ft. over SE. slope.
41.22	The center $\frac{1}{4}$ sec. cor. of sec. 8. Ascend 125 ft. over SE. slope.
43.70	Leave timber, edge bears N. and S.; enter logged area.
45.70	Ridge dividing Canyon Creek and Mitchell Creek drainage, bears N. 55° E. and S. 30° W.; desc. 905 ft. over broken NW. slope.
75.80	Creek, 1 lk. wide, course N.; asc. 355 ft. over NE. slope.
85.39	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8.