

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 8, T. 31 S., R. 5 W.

CHAINS

	From the center S 1/16 sec. cor. of sec. 8.
	N. 87° 58' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 8.
	Ascend 635 ft. over SE. slope, through heavy timber and dense undergrowth.
20.80	Ridge dividing Canyon Creek and Mitchell Creek drainage, bears N. 40° E. and S. 40° W.; desc. 285 ft. over broken NW. slope.
36.20	Ravine, drains N.; asc. 180 ft. over NE. slope.
44.20	Spur, slopes N. 25° W.; desc. 10 ft. over W. slope.
44.88	The S 1/16 sec. cor. of secs. 7 and 8.
	From the center N 1/16 sec. cor. of sec. 8.
	N. 88° 49' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 8.
	Descend 315 ft. over NW. slope, through heavy timber and dense undergrowth.
10.00	Creek, 1 lk. wide, course N. 20° W.; asc. 60 ft. over NE. slope.
13.70	Spur, slopes N. 20° W.; desc. 395 ft. over NW. slope.
27.45	Creek, 1 lk. wide, course N. 30° W.; asc. 80 ft. over NE. slope.
30.50	Spur, slopes N. 15° W.; desc. 170 ft. over NW. slope.
35.40	Creek, 4 lks. wide, course N. 20° W.; asc. 220 ft. over NE. slope.
43.37	The N 1/16 sec. cor. of secs. 7 and 8.
	Correction Survey of a Portion of the Subdivisional Lines of T. 31 S., R. 5 W.
	(Correcting the 1955 dependent resurvey by Hans W. Thielsen)
	From the cor. of secs. 2, 3, 34, and 35 on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., protruding 8 ins. above ground, firmly set, with brass cap mkd. and witnessed as described in the official record of 1955 resurvey.
	N. 0° 58' E., bet. secs. 34 and 35, marking and blazing the true line.
	Ascend 8 ft. over SW. slope, through heavy timber and dense undergrowth.
2.20	Top of ascent, slopes W.; desc. 385 ft. over NW. slope.
21.80	Spur, slopes N. 40° W.; desc. 125 ft. over N. slope.
24.90	Creek, 1 lk. wide, course N. 50° W.; asc. 25 ft. over SW. slope.

Feb. 7/73
 BLIND MONUMENT
 SET
 FILE