

County Surveyor's Record, Douglas County, Oregon

Correction survey, Portion Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS

28.60 Top of ascent, slopes W.; desc. 145 ft. over NW. slope.
 38.405 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.
 Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 34 | S 35
 1966
 1955

Feb. 20. 7/93
 BLM ADMIN. SURVEY
 SEE 575 FILE

from which

A fir, 12 ins. diam., bears S. 11° E., 5 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

A fir, 18 ins. diam., bears S. 54 $\frac{1}{2}$ ° W., 20 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

From this point, the point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, established in 1955, bears N. 18° 47' W., 0.525 chs. dist. Destroyed all marks on the 1955 bearing trees.

Descend 75 ft. over NW. slope.

42.20 Creek, 20 lks. wide, course NE.; asc. 130 ft. over SE. slope.
 49.65 Spur, slopes E.; desc. 120 ft. over NE. slope.
 52.20 Ravine, drains S. 80° E.; asc. 385 ft. over S. slope.
 62.00 Top of ascent, slopes SE.; asc. 130 ft. along E. slope.
 76.81 Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 31 S R 5 W
 S 27 | S 26
 S 34 | S 35
 1966
 1955

from which

A fir, 15 ins. diam., bears N. 46° E., 45 lks. dist., mkd. T31S R5W S26 BT.

A fir, 11 ins. diam., bears S. 68 $\frac{1}{2}$ ° E., 33 lks. dist., mkd. T31S R5W S35 BT.

A live oak, 8 ins. diam., bears S. 76 $\frac{1}{2}$ ° W., 17 lks. dist., mkd. T31S R5W S34 BT.

A fir, 10 ins. diam., bears N. 82° W., 61 lks. dist., mkd. T31S R5W S27 BT.

From this point, the point for the cor. of secs. 26, 27, 34, and 35, established in 1955, bears N. 18° 47' W., 1.05 chs. dist. Destroyed all marks on the 1955 bearing trees.