

County Surveyor's Record, Douglas County, Oregon

Correction Survey, Portion Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS

Ascend 50 ft. over SE. slope through light timber and dense undergrowth generally along W. edge of old logged area.

8.85 Apur, slopes NE.; desc. 890 ft. over NW. slope changing to N. slope.

30.10 Creek, 1 lk. wide, course N. 50° E.; asc. 190 ft. over SE. slope.

38.47 The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set by John M. Powell, Deputy County Surveyor, in 1966, protruding 8 ins. above ground, with brasscap mkd.

COUNTY SURVEYORS OFFICE

T 31 S

R 5 W

 $\frac{1}{4}$ S 27 | S 26

1966

from which the remaining original bearing tree

A fir snag, 24 ins. diam., bears S. 75° W., 45 lks. dist., with scribe marks S BT faintly visible on badly weathered bark blaze.

and bearing trees marked by Powell

A yew, 12 ins. diam., bears N. 32° E., 53 lks. dist., with scribe marks $\frac{1}{4}$ S26 CS BT visible on open double blaze.

A fir, 10 ins. diam., bears N. 69 $\frac{1}{2}$ ° W., 8 $\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S27 CS BT visible on open double blaze.

From this point the cor. of secs. 22, 23, 26, and 27, bears N. 0° 44' E., 40.39 chs. dist., monumented with an iron post, 2 ins. diam., protruding 8 ins. above ground, firmly set, with brass cap mkd. and witnessed as described in the official record of a 1955 resurvey.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, alder, live oak, and madrone; undergrowth, vine maple, huckleberry, arrowwood, hazel, salal, and fern.

From the cor. of secs. 26, 27, 34, and 35.

N. 87° 40' W., bet. secs. 27 and 34.

Ascend 285 ft. over E. slope through heavy second growth timber and dense undergrowth.

6.10 Spur, slopes N. 60° E.; desc. 120 ft. over NW. slope.

16.00 Bottom of descent, slopes N.; asc. 120 ft. over NE. slope.

24.30 Spur, slopes from N. 88° W., to S. 80° E.; also graveled road, 30 lks. wide, bears N. on curve to N. 20° W. and S. on curve to S. 65° W.; asc. 375 ft. along back of spur.

36.75 Spur ridge, bears N. 30° E. and S. 30° W.; desc. 65 ft. over NW. slope.

39.74 The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, determined at record bearing and distance from the remaining original bearing tree: