

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 30 S., R. 5 W.

CHAINS

- 27.80 Ravine, drains NE.; continue along E. slope changing to NE. slope.
- 31.90 Ravine, drains E.; asc. 40 ft. over SE. slope.
- 35.80 Spur, slopes N. 75° E.; desc. 90 ft. over N. slope.
- 38.30 Ravine, drains NE.; desc. 10 ft. along E. slope changing to NE. slope.
- 40.08 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- $\frac{1}{4}$
 S 35 | S 36
 T 30 S R 5 W
 1967
- from which
- A fir, 10 ins. diam., bears N. 46° E., 21 lks. dist., mkd.
 $\frac{1}{4}$ S36 BT.
- A fir, 35 ins. diam., bears N. 60 $\frac{1}{2}$ ° W., 76 $\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S35 BT.
- Descend 215 ft. over NE. slope.
- 45.20 Creek, 1 lk. wide, course NE.; desc. 135 ft. over broken NE. slope.
- 51.35 Creek, 1 lk. wide, course N. 75° E.; asc. 20 ft. over SE. slope.
- 53.40 Top of ascent, slopes NE.; desc. 255 ft. over N. slope.
- 60.12 Point for the N 1/16 sec. cor. of secs. 35 and 36.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- N 1/16
 S 35 | S 36
 1967
- from which
- A fir, 27 ins. diam., bears S. 80 $\frac{1}{2}$ ° E., 63 lks. dist.,
mkd. N 1/16 S36 BT.
- A fir, 60 ins. diam., bears N. 72° W., 21 lks. dist.,
mkd. N 1/16 S35 BT.
- The cor. falls at the cor. of logged area, edge bears S. and W.
- Descend 260 ft. over N. slope.
- 65.65 O'Shea Creek, 15 lks. wide, course N. 55° W.; asc. 200 ft. over broken SW. slope.
- 66.75 Gravelled road, 15 lks. wide, bears NW. and SE.
- 67.00 Wire fence, bears NW. and SE.
- 77.00 Spur, slopes W.; desc. 55 ft. over NW. slope.
- 79.70 Spring seepage, 2 lks. wide, course W.; continue along W. slope.